

## Biomax Pack (Product Number: 779194)



Applications	Sewage Treatment			Accommodation		Product Recommendation And Benefits	Product Number	Dosing Instructions*
	Treatment Plants	Holding Tanks	Pipe Cleaning	Sinks, Showers, Drain Lines, Scuppers	Toilet And Rest Room			
Marine Sewage Treatment Plants	*	<b>~</b>	<b>~</b>			Gamazyme 700 FN  Increases treatment plant performance  Greatly increases the degradation of organics commonly found in waste water (starch, protein, cellulose, fats, oils, greases, hydrocarbons, detergents, sulphide, paper)  Stabilizes existing biomass and maximizes its degrading abilities (bio-augmentation) / plant start-up, maintenance and upset recovery  Quantity in Biomax: 1 x 12 KG	571711	Direct dosing to Sewage Treatment Plant or via the nearest toilet - Maintenance dosing of 0.1 - 0.25kg weekly will keep the system operating effectively (for passenger vessels please see product data sheet for correct dosage)
Drain Lines, Holding Tanks		<b>~</b>	~	<b>~</b>		Gamazyme DPC (Drain and Pipe Cleaner)  • Keeps sinks, drains and pipes - black and gray water tanks free of organic matters (fats, grease, starch, organic waste)  • Eliminates malodours from showers, sinks and drains Quantity in Biomax: 2 x 4 KG	587055	A liquid solution should be prepared by adding one solupac to 10 litres of hand hot (35°C) fresh water and left for 15 minutes (stirring periodically) for the bacteria to activate. Initial doses of 0.5 litres of this solution should be applied into sinks, scuppers, drains, waste food disposal units, etc. A maintenance dose once or twice a week can then be applied to keep the pipes in clean condition.
Toilets, Drain Lines				<b>~</b>	~	Gamazyme BTC (Biological Toilet Cleaner)  • Keeps toilet bowls, sinks and urinals cleaned  • Eliminates bad odours  Quantity in Biomax: 2 X 12 X 1 LTR	589945	Use Gamazyme BTC daily as a normal toilet clearner. Lift up seat, open the bottle and direct nozzle downwards. Squeeze and direct the jet to adequately cover the surface of the toilet bowl. After some minutes scrub vigorously with a toilet brush and flush with water.
	*For detailed (	dosing instru	ctions please c	:heck product data she	<b>✓</b> ets	Cleans up toilet and drain lines fouled with scale and organic matters - dual action:  The mild acid component dissolves the rust stains and water scale  The selected microorganisms digest the organic waste  Quantity in Biomax: 4 X 5 KG	743146	<ul> <li>Descaling of toilet bowl</li> <li>Add 50 grams (one sachet) to each toilet once a week as a minimum.</li> <li>Let sachet stand for 1 min. for complete dissolution.</li> <li>Brush the bowl and flush water into the toilet.</li> <li>Repeat the treatment if necessary.</li> </ul>

Wilhelmsen Ships Service T +47 67 58 40 00 F +47 67 58 40 80 PO Box 33, NO-1324 Lysaker, Norway

wilhelmsen.com

