

Product group: 401 Product number: 671768

Reinforced rubber hose.

Product information

This product supersedes product no: 181693



Specification

General

Invent Hazard Material (IMO/IU) classification	NA
Material	Black NBR Rubber

Dimensions/Weight

Diameter [mm]	12.5
---------------	------

Technical data

Burst pressure [bar]	6.0 Mpa / 60 BAR
Test Pressure [bar]	4.0 Mpa / 40 BAR

Made of SBR&NBR rubber with a synthetic reinforcement, comes in coil of 50 m. working pressure 1.5 Mpa or up to 15 BAR. More flexible than PVC. Keeps flexibility even in cold weather, and it has excellent resistance towards mechanical wear. Excellent for maritime / shipping, offshore oil and gas.

Performance data

Working Pressure	1.5 Mpa / 15 BAR
------------------	------------------

Documents

[Declaration of conformity for Rubber hose](#)

[SDoC and MD for IHM](#)

Related products

Accessories

- 191692**
40 USH SOCKET 1/2" HOSE
- 768457**
CLAMP 1 EAR 22-24.8 MM 1/2 " HOSE (20 PCS)
- 729444**
HOSE CLAMP FOR 1/2" HOSE (10 PCS)
- 768507**
PINCER TOOL FOR EAR TYPE HOSECLAMPS
- 191841**
40 UPH PLUG 1/2" HOSE

Is accessory to

- 778893**
1:1 OIL PUMP W/SPOUT FOR 200L DRUM
- 658229**
TORNADO 3 CARGO HOLD CLEANING JET
- 604926**
DOUBLE DIAPHRAGM PUMP 2150 ALU
- 191700**
400 USH SOCKET 1/2" HOSE
- 722199**
IMPACT WRENCH IW-PRO 1"
- 721977**
ANGLE GRINDER AG-PRO 7

Is frequently bought together with

- 191874**
20 UPMPLUG 1/4" MALE BSP.T
- 191890**
40 UPMPLUG 1/2" MALE BSP.T
- 191684**
30 USH SOCKET 3/8" HOSE

