

Product group: 401      Product number: 671743

Reinforced rubber hose.



Product information

Benefits

- Made of oil resistant rubber
- Temperature range -20°C - +60°C

Specification

General

Invent Hazard Material (IMO/IU) classification	NA
Material	Black NBR Rubber

Dimensions/Weight

Diameter [mm]	6.3
---------------	-----

Technical data

Burst pressure [bar]	6.0 Mpa / 60 BAR
Test Pressure [bar]	4.0 Mpa / 40 BAR

Performance data

Working Pressure	1.5 Mpa / 15 BAR
------------------	------------------

Made of SBR&NBR rubber with a synthetic reinforcement, comes in coil of 50 m. working pressure 1.5 Mpa or up to 15 BAR. More flexible than PVC. Keeps flexibility even in cold weather, and it has excellent resistance towards mechanical wear. Excellent for maritime / shipping, offshore oil and gas.

Documents

[Declaration of conformity](#)

[SDoC and MD for IHM](#)

Related products

Accessories

- 191825**  
20 UPH PLUG 1/4" HOSE
- 768416**  
CLAMP 1 EAR 12,3-14,3MM 1/4" HOSE (20PCS)
- 729442**  
HOSE CLAMP FOR 1/4" HOSE (10 PCS)
- 768507**  
PINCEER TOOL FOR EAR TYPE HOSECLAMPS
- 191676**  
20 USH SOCKET 1/4" HOSE

Is frequently bought together with

- 191841**  
40 UPH PLUG 1/2" HOSE
- 191874**  
20 UPMPLUG 1/4" MALE BSP.T
- 632786**  
WELDERS GLOVES. 6 PAIRS