

Product group: 482 Product number: 658229

The Unitor™ Tornado 3™ has been designed for use on board medium to large bulk carriers. Shut off ball valve for both air and water supply is mounted on the Tornado for increased safety and simpler operations.

Product information

The intended use is cleaning and descaling of cargo holds. It uses the suppression pump as a water source. This enables the jet to reach the top of the hold and at the same time giving the capacity needed to remove even the most stubborn dirt or scale.

Suitable couplings for air and water supply are listed under accessories.

Features

- Stainless steel design
- Swivel connection between gun and tripod
- Works on normal fire line and working air line on board
- High water volume

- Long operating life with minimum maintenance Easy to set-up and connect without any additional equipment
- Enables crew to clean cargo holds quickly
- Easy to use, aim and transport and does not require any special training

Specification

General

Invent Hazard Material (IMO/EU) classification	NA

Air consumption [m³/min]	2
Air inlet connection [inch]	3/4
Air pressure [bar]	
Feed water pressure [bar]	
Water inlet connection [inch]	

Technical data

Documents

733HY01A

SDoC and MD for IHM

Related products

Accessories

191965

600 UPF PLUG 3/4" FEMALE BSP.T

191700

400 USH SOCKET 1/2" HOSE

191858

400 UPH PLUG 1/2" HOSE

671768

AIR HOSE 1/2", RUBBER, 50 METER COIL

510737

CLEANING HOSE 2" W/STORZ C CPL 15MTR

333975

STORZ C CPL W/2" MALE THREAD ALU

729444

HOSE CLAMP FOR 1/2" HOSE (10 PCS)

Is accessory to

778955

UNITOR CARGO HOLD COMPACT KIT

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/cleaning-equipment/cargo-hold-cleaning-jets/tornado-3-cargo-hold-cleaning-jet/