

Last updated: 30/04/2025 05:22:56

UNITOR HPC 30/1 220V/60Hz

Product group: **430** Product number: **729333**

Compact and lightweight, it's ideal for quick, spot cleaning in areas like the engine room and accommodation decks, making it the go-to solution for small, on-the-spot tasks onboard



Product information

This product supersedes product no: **729327**

The HP Cleaner Unitor™ HPC 30/1 has 20 % stronger water jet compared to previous model. Higher effect reducing cleaning time and hence labor costs.

The high pressure washer can be used where electrical power supply is limited. Ideal for use as an extra machine or in areas where space is limited and larger machines are not appropriate, e.g. engine rooms and accommodation decks.

Practical transport handle making storage and transport easy. The with large wheels helps to increase mobility and stability.

The pump has 3 stainless steel pistons, long life pump for light cleaning tasks onboard.

Unitor™ HPC 30/1 is supplied with a 2,5 ltr bottle for foaming application. The bottle can be attached to the gun. Foaming makes cleaning easier and more efficient. When parked, the bottle can be stored on the back of the machine.

Practical storage for cable and hose enhances mobility. The built in lance holder provides ideal storage and protects lance from damage.

Supplied with

- Tornado lance
- Spray handle
- Quick coupling
- 10m HP hose
- 10m Electrical Cable
- Water Inlet coupling

Features

- Innovative foam sprayer
- Washable feed water filter 50µ
- Oil level indicator
- Stainless steel pistons
- Pressure gauge

Benefits

- Light and compact - easy to transport and store
- Fast to connect - saves time
- Ideal for areas with limited space
- Ergonomic design - improves work capabilities

Specification

General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

Dimensions/Weight

Dimensions L x W x H [mm]	382 x 382 x 1017
Weight [kg]	35.7

Technical data

Frequency [Hz]	60
Ingress protection	5X
Inlet water temperature [°C]	60 maximum
Operating pressure [bar]	150
Power rating [kW]	3.5
Voltage [V]	220 mains supply
Water flow rate [l/min]	11 maximum
Water pressure [bar]	200 maximum

Approvals

Corresponds to the following pertinent regulations:

EC Machine Directive 2006/42/EC

EC Low-voltage Directive 2006/95/EC

EC EMC Directive 2004/108/EC

EC RoHS Directive 2011/65/EC

Applied harmonised standards:

EN 12100, EN 60335-2-79, EN 55014-1, EN 55014-2, EN 61000-3-2

Applied national standards and technical specifications:

DIN EN 60335-2-79

Documents

[SDoC and MD for IHM](#)

[UNITOR-HPC-30-1-User-Manual](#)

Directions for use

Oil change: use oil SAE 80W-90. Oil capacity 0,42 liter, Feed water temperature max 60C. For operation exceeding one hour max 40C is allowed.Always refer to user manual.

Related products

Accessories

671735
AIR HOSE 1", PVC 50 M COIL

671727
AIR HOSE 3/4", PVC 50 M COIL

659151
EXTENDABLE LANCE 5.5M W/OUT NOZZLE

621938
LONG REACH LANCE

545335
FOAM INJECTOR DETACHABLE

545343
FOAM LANCE 120CM LONG

621896
HOSE CART, MOBILE

546036
COUPLING KIT ERGO 3000

665158
ERGO 3000 SPRAY GUN

636159
DOUBLE LANCE F/HPC 30CA-1PH

718585
NOZZLE 05/25DGR. F/EXTENDABLE LANCE

718601
NOZZLE 05/0DGR. F/EXTENDABLE LANCE

571729
HP WASH 25 LTR

546044
WASHING BRUSH 235CMLONG

550030
UNITOR HEAVY DUTY HOSE 250BAR BLUE 25M

550035
UNITOR HEAVY DUTY HOSE 250BAR 25M

550040
UNITOR HEAVY DUTY HOSE 250BAR 15M

Is frequently bought together with

546036
COUPLING KIT ERGO 3000

571729
HP WASH 25 LTR