

Product group: 430 Product number: 777888

The new Unitor™ HPC 67/1 is a heavy duty cold water high pressure washer that combine renowned lifetime and quality. Optimal ergonomics and mobility offer an innovative partner for applications onboard all vessel types.

Product information

This product supersedes product no: 652594

The Unitor™ HPC 67/1 is equipped with the 4 ceramic pistons pump, double roller bearings, flow activated unloader system and 1750 rpm motor for high intensity use with maximum performance and comfort. Capable of accepting 85°C inlet water, the Unitor™ HPC 67/1 can be used as an effective hot water cleaner. At 85°C degreasing can be performed without usage of chemicals. The new chemical system allows two different chemicals. If higher volume is needed the suction hose in the tank can be place in a larger canister.

The unit is equipped with additional motor protection for supurb marine operational safety.

The Unitor™ HPC 67/1 gives you high cleaning efficiency combined with reduced downtime and increased lifetime. Unitor™ HPC 67/1 comes with a castor wheel with brake for high mobility and safety.

Supplied with

- Tornado lance
- Spray handle
- Quick coupling
- 10m HP hose
- Water inlet coupling

Features

- High mobility and ergonomic design
- · 4 full ceramic piston pump -- ensures long unit life
- Up to 85° C inlet water
- Two tank chemical dosing

Benefits

- Effectively removes intense dirt
- · Reduces cleaning time cleanes faster
- Reduces water consumption compared to conventional cleaning
- · Designed for intense applications up to 8 hours continuous operation

Specification

General

| Invent Hazard Material (IMO/EU) classification | D-1 |
|--|-----|
| | |

Dimensions/Weight

| Dimensions L x Wx H [mm] | 775 x 570 x 1020 |
|--------------------------|------------------|
| Nozzle size | 0680 |
| Weight [kg] | 90 |

Technical data

| Amperage [A] | 11.4 |
|-------------------------------|------|
| Cleaning impact [kg] | 6,7 |
| Frequency [Hz] | 50 |
| Ingress protection | X5 |
| Inlet water temperature [°C] | |
| Operating pressure [bar] | 195 |
| Power rating [kW] | 8 |
| Voltage [V] | |
| Water flow rate [l/min] | 21.3 |
| Water inlet connection [inch] | 3/4 |

Performance data

| Rotation speed | 1450 rpm | |
|----------------|----------|--|
| | | |



Approvals

Corresponds to the following pertinent regulations:

EC Machine Directive 2006/42/EC

EC Low-voltage Directive 2006/95/EC

EC EMC Directive 2004/108/EC

EC RoHS Directive 2011/65/ECEC

Machine Directive 2006/42/EC

EC Low-voltage Directive 2006/95/EC

EC EMC Directive 2004/108/EC

EC RoHS Directive 2011/65/EC

Applied harmonised standards:

EN ISO 12100-1, EN ISO 12100-2, EN 60335-2-79, EN 55014-1(2002), EN 55014-2(2001), EN 61000-3-2 (2006)

Applied national standards and technical specifi cations:

IEC 60335-2-79

Documents

HPC-UNITOR-54-67EN-DE-FRv01

SDoC and MD for IHM

Directions for use

See user manual for details.

Oil: Castrol AlphaSyn 150

Related products

Accessories

546036

COUPLING KIT ERGO 3000

586792

HEAVY DUTY HOSE 15 MTR

EXTENDABLE LANCE 5.5MW/OUT NOZZLE

586784

HEAVY DUTY HOSE 25 MTR

571729

HP WASH 25 LTR

AIR HOSE 1"", PVC 50 M COIL

AIR HOSE 3/4"", PVC 50 M COIL

671818

HEAVY DUTY HOSE, BLUE 25M

621813

DRAIN CLEANER 6401266 F/HPC 54, 20M

718577

NOZZLE 06/25DGR. F/EXTENDABLE LANCE

545335

FOAMINJECTOR DETACHABLE

718593

NOZZLE 06/0DGR. F/EXTENDABLE LANCE

621938

LONG REACH LANCE

545343

FOAMLANCE 120CMLONG

682070

UNIVERSAL.3000 LANCE 06 NOZZLE

665158

ERGO 3000 SPRAY GUN

659128

POWERSPEED LANCE WITH 06 NOZZLE

621896

HOSE CART, MOBILE

659110

TORNADO LANCE 92CM WITH 06 NOZZLE

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/cleaning-equipment/mobile-high-pressure-cleaners/hp-cleaners-150---220-bar/unitor-hpc-671-3x40050hz/