

Product group: 430 Product number: 777889

The new Unitor™ HPC 67/1 is a heavy duty cold water high pressure washer that combine renowned lifetime and quality. Optimal ergonomics and mobility offer an innovative partner for applications onboard all vessel types.

Product information

This product supersedes product no: 652586

The Unitor™ HPC 67/1 is equipped with the 4 ceramic pistons pump, double roller bearings, flow activated unloader system and 1750 rpm motor for high intensity use with maximum performance and comfort. Capable of accepting 85°C inlet water, the Unitor™ HPC 67/1 can be used as an effective hot water cleaner. At 85°C degreasing can be performed without usage of chemicals. The new chemical system allows two different chemicals. If higher volume is needed the suction hose in the tank can be place in a larger canister.

The unit is equipped with additional motor protection for extra marine operational safety.

The Unitor™ HPC 67/1 gives you high cleaning efficiency combined with reduced downtime and increased lifetimebeing tailor made for Mariner applications in the Engine or on Deck. Unitor™ HPC 67/1 comes with a castor wheel with brake for high mobility and safety.



Supplied with

- Tornado lance
- Spray handle
- Quick coupling
- 10m HP hose
- Water inlet coupling

Features

- High mobility and ergonomic design
- 4 full ceramic piston pump – ensures long unit life
- Up to 85° C inlet water
- Two tank chemical dosing

Benefits

- Effectively removes intense dirt
- Reduces cleaning time - cleans faster
- Reduces water consumption compared to conventional cleaning
- Designed for intense applications up to 8 hours continuous operation

Specification

General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

Dimensions/Weight

Dimensions L x W x H [mm]	775 x 570 x 1020
Nozzle size	0680
Weight [kg]	90

Technical data

Amperage [A]	11.4
Cleaning impact [kg]	6,7
Ingress protection	X5
Inlet water temperature [°C]	
Operating pressure [bar]	195
Power rating [kW]	8
Water flow rate [l/min]	21.3
Water inlet connection [inch]	3/4

Performance data

Rotation speed	1750
----------------	------

Approvals

Corresponds to the following pertinent regulations:

EC Machine Directive 2006/42/EC

EC Low-voltage Directive 2006/95/EC

EC EMC Directive 2004/108/EC

EC RoHS Directive 2011/65/ECEC

Machine Directive 2006/42/EC

EC Low-voltage Directive 2006/95/EC

EC EMC Directive 2004/108/EC

EC RoHS Directive 2011/65/EC

Applied harmonised standards:

EN ISO 12100-1, EN ISO 12100-2, EN 60335-2-79,
EN 55014-1(2002), EN 55014-2(2001), EN 61000-3-2 (2006)

Applied national standards and technical specifications:

IEC 60335-2-79

Documents

HPC-UNITOR-54-67EN-DE-FRW01

SDoC and MD for IHM

Directions for use

See user manual for details.

Related products

Accessories

671735
AIR HOSE 1''' , PVC 50 M COIL

671727
AIR HOSE 3/4''' , PVC 50 M COIL

659151
EXTENDABLE LANCE 5.5M W/OUT NOZZLE

571729
HP WASH 25 L TR

621896
HOSE CART, MOBILE

546036
COUPLING KIT ERGO 3000

545335
FOAM INJECTOR DETACHABLE

665158
ERGO 3000 SPRAY GUN

621938
LONG REACH LANCE

682070
UNIVERSAL.3000 LANCE 06 NOZZLE

718577
NOZZLE 06/25DGR. F/EXTENDABLE LANCE

621813
DRAIN CLEANER 6401266 F/HPC 54, 20M

718593
NOZZLE 06/0DGR. F/EXTENDABLE LANCE

659110
TORNADO LANCE 92CM WITH 06 NOZZLE

659128
POWERSPEED LANCE WITH 06 NOZZLE

586792
HEAVY DUTY HOSE 15 MTR

671818
HEAVY DUTY HOSE, BLUE 25M

545343
FOAM LANCE 120CM LONG

586784
HEAVY DUTY HOSE 25 MTR

