

Last updated: 22/10/2025 14:18:14

UNITOR HPC STATIONARY 4P

Product group: **435** Product number: **729404**

The Unitor™ HPC Stationary 4P is a flexible pump station that is capable of supplying up to 4 simultaneous operators with pressurized water for high pressure cleaning. Dependant on the amount of operators performing high pressure cleaning on board the vessel, the Unitor™ HPC Stationary detects the line pressure drop and will automatically activate the number of pumps being required.



Product information

This product supersedes product no: **613804**

Four pump stationary cold water unit for medium and heavy cleaning applications in maritime use.

The Unitor Stationary 4P model is for heavy cleaning applications with up to 4 users at same time.

Features

- Stainless steel frame and robust cabinet ensure that pumps and electronics are well-protected
- 4 pump system, each pump is equipped with four solid ceramic pistons
- Supplied with both cold and hot water inlet valves
- Smart pump control system with touch screen at front panel
- Line pressures can be adjusted
- As water requirement drops, pumps will stop automatically
- Pumps operate on rotation to avoid excessive wear on single pumps
- The lower front panel can be opened for easy access to the pumps
- High level of serviceability, pumps and motors are quickly and easily removed

Benefits

- The pumps are installed on the frame with rubber dampers, and flexible connections to power and water
- Smart control system detects the amount of water required by the relevant number of operators and start the required pumps automatically
- Long life pump for intense applications
- Efficient operation and routine maintenance
- Up to 4 simultaneous operators

Specification

General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

Dimensions/Weight

Height [mm]	1800
Length [mm]	970
Weight [kg]	408
Width [mm]	1050

Technical data

Amperage [A]	58
Electrical phase	3
Frequency [Hz]	60
Ingress protection	X5
Inlet water temperature [°C]	89 maximum
Operating pressure [bar]	200
Power rating [kW]	35
Voltage [V]	440 mains supply
Water flow rate [l/min]	85 maximum

Documents

[SDoC and MD for IHM](#)

[Instruction manual](#)

Related products

Accessories

718577

NOZZLE 06/25DGR. F/EXTENDABLE LANCE

621821

DRAIN CLEANER F/HPC 67/HPC 61 HW/STATIONERY, 20M

659151

EXTENDABLE LANCE 5.5MW/OUT NOZZLE

621938

LONG REACH LANCE

546150

DOUBLE LANCE 200CMLONG 064 NOZZLE

623595

TAKE OFF VALVE 6402023 ACID PROOF 316

665158

ERGO 3000 SPRAY GUN

659128

POWERSPEED LANCE WITH 06 NOZZLE

623603

TAKE OFF VALVE 6402024 CHR. PLATED BRASS

545327

CHEM INJECTOR DETACHABLE

545335

FOAMINJECTOR DETACHABLE

545434

DOUBLE LANCE 10CMLONG 06 NOZZLE

545343

FOAMLANCE 120CMLONG

546044

WASHING BRUSH 235CMLONG

621896

HOSE CART, MOBILE

682070

UNIVERSAL.3000 LANCE 06 NOZZLE

546036

COUPLING KIT ERGO 3000

718593

NOZZLE 06/0DGR. F/EXTENDABLE LANCE

633995

Q. COUPLING, MALE 3/4"

550030

UNITOR HEAVY DUTY HOSE 250BAR BLUE 25M

550035

UNITOR HEAVY DUTY HOSE 250BAR 25M

550040

UNITOR HEAVY DUTY HOSE 250BAR 15M

770008

UNITOR DYNAMIS/ PPE KIT 500 BAR

545025

HOSE PROTECTION 1400MM Ø41 – 500 BAR WITH ADJUSTABLE STRAP

659110

TORNADO LANCE 92CM WITH 06 NOZZLE

Consumables

571729

HP WASH 25 LTR

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/cleaning-equipment/stationary-high-pressure-systems/stationary-cold-water-cleaners/unitor-hpc-stationary-4p/>