

Last updated: 26/02/2025 17:55:08

UNITOR HPC STATIONARY 6P

Product group: **435** Product number: **729406**

The Unitor™ HPC Stationary 6P is a flexible pump station that is capable of supplying up to 6 simultaneous operators with pressurized water for high pressure cleaning. Dependant on the amount of operators performing high pressure cleaning on board the vessel, the Unitor™ HPC Stationary detects the line pressure drop and will automatically activate the number of pumps being required.



Product information

This product supersedes product no: **613806**

Six pump stationary cold water unit for medium and heavy cleaning applications in maritime use.

The Unitor Stationary 6P model is for heavy cleaning applications with up to 6 users at same time.

Features

- Stainless steel frame and robust cabinet that ensure pumps and electronics are well-protected
- 6 pump system, each pump is equipped with four solid ceramic pistons
- Supplied with both cold and hot water inlet valves
- Smart pump control system with touch screen at the front panel
- Line pressures can be adjusted
- As water requirement drops, pumps will stop automatically
- Pumps operate on rotation to avoid excessive wear on single pumps
- The lower front panel can be opened for easy access to the pumps
- High level of serviceability, pumps and motors are quickly and easily removed

Benefits

- The pumps are installed on the frame with rubber dampers, and flexible connections to power and water
- Smart control system detects the amount of water required by the relevant number of operators and start the required pumps automatically
- Long life pump for intense applications
- Efficient operation and routine maintenance
- Up to 6 simultaneous operators

This bundle contains:

729404
UNITOR HPC STATIONARY 4P

Specification

General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

Dimensions/Weight

Height [mm]	1800
Length [mm]	970
Weight [kg]	526
Width [mm]	1050

Technical data

Amperage [A]	87
Electrical phase	3
Frequency [Hz]	60
Ingress protection	X5
Inlet water temperature [°C]	70 maximum
Operating pressure [bar]	200
Power rating [kW]	53
Voltage [V]	440 mains supply
Water flow rate [l/min]	128,3 maximum

Documents

[SDoC and MD for IHM](#)

[Instruction manual](#)

Related products

Accessories

718577
NOZZLE 06/25DGR. F/EXTENDABLE LANCE

621821
DRAIN CLEANER 6401268 F/HPC 67, 20M

659151
EXTENDABLE LANCE 5.5M W/OUT NOZZLE

671818
HEAVY DUTY HOSE, BLUE 25M

621938
LONG REACH LANCE

662163
TORNADO LANCE 92CM WITH 05 NOZZLE

546150
DOUBLE LANCE 200CMLONG

623595
TAKE OFF VALVE 6402023 ACID PROOF 316

665158
ERGO 3000 SPRAY GUN

659128
POWERSPEED LANCE WITH 06 NOZZLE

623603
TAKE OFF VALVE 6402024 CHR. PLATED BRASS

545327
CHEM. INJECTOR DETACHABLE

586792
HEAVY DUTY HOSE 15 MTR

545335
FOAM INJECTOR DETACHABLE

545434
DOUBLE LANCE 10CMLONG

586784
HEAVY DUTY HOSE 25 MTR

545343
FOAM LANCE 120CMLONG

546044
WASHING BRUSH 235CMLONG

621896
HOSE CART, MOBILE

682070
UNIVERSAL.3000 LANCE 06 NOZZLE

546036
COUPLING KIT ERGO 3000

718593
NOZZLE 06/0DGR. F/EXTENDABLE LANCE

565861
RUBBER NOZZLE F/VSF 300

621904
HOSE, HP OUTLET

633995
Q. COUPLING, MALE 3/4"

550030
UNITOR HEAVY DUTY HOSE 250BAR BLUE 25M

550035
UNITOR HEAVY DUTY HOSE 250BAR 25M

550040
UNITOR HEAVY DUTY HOSE 250BAR 15M

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/cleaning-equipment/stationary-high-pressure-systems/stationary-cold-water-cleaners/unitor-hpc-stationary-6p/>