

Product group: **435** Product number: **729406**

The Unitor™ HPC Stationary 6P is a flexible pump station that is capable of supplying up to 6 simultaneous operators with pressurized water for high pressure cleaning. Dependant on the amount of operators performing high pressure cleaning on board the vessel, the Unitor™ HPC Stationary detects the line pressure drop and will automatically activate the number of pumps being required.

## Product information

This product supersedes product no: **613806**

Six pump stationary cold water unit for medium and heavy cleaning applications in maritime use.

The Unitor Stationary 6P model is for heavy cleaning applications with up to 6 users at same time.

### Features

- Stainless steel frame and robust cabinet ensuring that pumps and electronics are well protected
- 6 pump system, each pump is equipped with four solid ceramic pistons
- Smart pump control system with touch screen at front panel
- Line pressures can be adjusted
- As water requirement drops, pumps will stop automatically
- Pumps operate on rotation to avoid excessive wear on single pumps
- The lower front panel can be opened for easy access to the pumps
- High level of serviceability, pumps and motors are quickly and easily removed

### Benefits

- The pumps are installed on the frame with rubber dampers, and flexible connections to power and water
- Smart control system detects the amount of water required by the relevant number of operators and start the required pumps automatically
- Long life pump for intense applications
- Efficient operation and routine maintenance
- Up to 6 simultaneous operators

This bundle contains:

**729404**

UNITOR HPC STATIONARY 4P

## Specification

### General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

### Dimensions/Weight

Height [mm]	1800
Length [mm]	970
Weight [kg]	526
Width [mm]	1050

### Technical data

Amperage [A]	87
Electrical phase	3
Frequency [Hz]	60
Ingress protection	X5
Inlet water temperature [°C]	70 maximum
Operating pressure [bar]	200
Power rating [kW]	53
Voltage [V]	440 mains supply
Water flow rate [l/min]	128,3 maximum

## Documents

[SDoC and MD for IHM](#)

[Instruction manual](#)

## Related products

### Accessories

- 546036**  
COUPLING KIT ERGO 3000
- 586792**  
HEAVY DUTY HOSE 15 MTR
- 659151**  
EXTENDABLE LANCE 5.5MW/OUT NOZZLE
- 586784**  
HEAVY DUTY HOSE 25 MTR
- 671818**  
HEAVY DUTY HOSE, BLUE 25M
- 621821**  
DRAIN CLEANER 6401268 F/HPC 67, 20M
- 718577**  
NOZZLE 06/25DGR. F/EXTENDABLE LANCE
- 545335**  
FOAM INJECTOR DETACHABLE
- 565853**  
LANCE F/VSF 300 03K
- 546044**  
WASHING BRUSH 235CMLONG
- 545434**  
DOUBLE LANCE 10CMLONG
- 718593**  
NOZZLE 06/0DGR. F/EXTENDABLE LANCE
- 623595**  
TAKE OFF VALVE 6402023 ACID PROOF 316
- 621938**  
LONG REACH LANCE
- 662163**  
TORNADO LANCE 92CM WITH 05 NOZZLE
- 545343**  
FOAM LANCE 120CMLONG
- 682070**  
UNIVERSAL.3000 LANCE 06 NOZZLE
- 665158**  
ERGO 3000 SPRAY GUN
- 546150**  
DOUBLE LANCE 200CMLONG
- 545327**  
CHEM. INJECTOR DETACHABLE
- 565861**  
RUBBER NOZZLE F/VSF 300
- 545640**  
SUCTION HOSE&ROD F/VSF300
- 623603**  
TAKE OFF VALVE 6402024 CHR. PLATED BRASS
- 659128**  
POWERSPEED LANCE WITH 06 NOZZLE
- 621896**  
HOSE CART, MOBILE

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/cleaning-equipment/stationary-high-pressure-systems/stationary-cold-water-cleaners/unitor-hpc-stationary-6p/>