

# NOX GUARD AUS40% UREA

Product group: 370 Product number: 912001

NOX GUARD AUS40% UREA reduces nitrogen oxide (NOx) emissions in marine diesel engines to help vessels stay compliant with IMO Tier III requirements.



## Product information

NOX GUARD AUS40% UREA reduces nitrogen oxide (NOx) emissions in marine diesel engines. Compliant with ISO 18611 standards, this product uses a 40% urea solution to support NOx emissions reduction, assisting your vessels in meeting existing NECA (Nitrogen Oxide Emission Control Areas) regulatory requirements.

### Features

- Product available in liquid form and has concentration of 39-41% Urea
- Designed to be used in Selective Catalytic Reduction (SCR) systems
- Reduces NOx emissions in line with IMO Tier III requirements
- Supplied in 1000 LTR IBCs or Tank Trucks depending on terminal restrictions

### Benefits

- Trusted quality - ISO 18611 certified for reliability and performance
- NOx emissions management - ensures compliance with IMO Tier III requirements

## Specification

### Physical properties

Colour	Colourless
Concentration	39 - 41% urea content
Density [kg/m <sup>3</sup> ]	1105 - 1177
Form	Liquid

## Approvals

ISO 18611 certified  
IMO Tier III compliant

## Documents

[NOx Guard AUS 40% Flyer](#)

[NOX Guard Certificate of conformity](#)

[NOX Guard Storage and Handling guidelines](#)

[NOX Guard IHM](#)

## Directions for use

Product is ready to use. Can be dosed directly into the SCR.