

Product group: 719 Product number: 905695

Carbon dioxide is used to carbonate beverages as well as in potable water plants to control acidity (pH). When welding (MAG) low carbon steel, CO₂ is also used as shielding gas. This product is delivered in a Unitor cylinder as part of WSS global cylinder exchange program.



Product information

Beverage grade carbon dioxide (CO₂) comes with a purity of 99.5%. This product is delivered in a 40 litre cylinder. CO₂ is a liquified gas, it liquifies under high pressure. A full cylinder contains 27kg of CO₂. Beware of asphyxiation hazards when using the gas. Expansion of liquid CO₂ into gas phase will result in a drop in temperatures.

Features

- Colourless, odourless and an incombustible gas
- CO₂ cylinders are fitted with handwheel operated valves and an American type side connection
- A regulator for this type of cylinder is available under product no. 698 510004

Benefits

- Typical in use for carbonation of beers and fizzy drinks on board Cruise ships.
- In use for potable water treatment to control acidity.
- Additionally can be used for MAG welding.
- For your safety, the product is delivered in a Unitor exchange cylinder complete with barcode and unique cylinder serial number
- We trace and track all cylinders using our system to give you peace of mind
- We offer global availability through our Global Exchange Programme.

Specification

General

Cylinder Type	C-27
Invent Hazard Material (IMO/IU) classification	C-22

Physical properties

Colour	Grey
--------	------

Dimensions/Weight

Connection [Size/ Type]	CGA320
Diameter [mm]	229
Gross Weight [kg]	82
Height [mm]	1350
Weight [kg]	

Technical data

Connection [inch]	
Filling pressure [bar]	--
Purity	2.5 > 99.5 %
Volume (l)	40

Performance data

Gas Capacity [m³]	14.9
-------------------	------

Documents

- [CO2](#)
- [SDoC and MD for IHM](#)

Related products

Accessories

- 510004
REGULATOR 510 CO2 FOR C-9 AND C-27 CYLINDER
- 510012
REGULATOR 510 CO2 FLOW CGA320

Is frequently bought together with

- 905034
OXYGEN O-40 FILLING
- 905067
ACETYLENE A-5 FILLING
- 905565
ARGON E-10 FILLING
- 905075
OXYGEN O-5 FILLING

