

Last updated: 30/04/2025 05:21:37

# NITROGEN N-5030 FILLING

# Product group: **714** Product number: **905208**

Nitrogen 3.0 grade is predominantly used for purging. This product is delivered in a Unitor cylinder as part of WSS global cylinder exchange program.

### **Product information**

Nitrogen in 3.0 Grade has 99.9% purity. This product is delivered in a 50 litre cylinder. Product does not come with a certificate to confirm its purity. An inert gas, it is normally used for purging and blanketing applications. Beware of asphyviation hazards when using the gas.

#### Features

- Nitrogen is a colourless, odourless and tasteless
- Non-combustible and non-toxic
- Slightly lighter than air and it's an inert gas
- Nitrogen is well suited for purging or flushing cargo tanks and pipelines of residual gases and vapours prior to loading cargo or doing maintenance
- It is also used as a 'blanket' on top of several types of cargoes to prevent reactions with oxygen from atmospheric air.
- The filling pressure is lower in some locations than the normal 200 bar due to local rules and regulations that limit filling pressure.
- Nitrogen 3.0 means > 99.9% pure and the impurities: Water (H2O) < 1000 ppm and Oxygen (O2) < 1000 ppm.

#### Benefits

- Perfectly suited for purging, inerting / blanketing
- For your safety, the product is delivered in a Unitor exchange cylinder complete with barcode and unique cylinder serial number
- We trace and track all cylinders using our system to give you peace of mind
- We offer global availability through our Global Exchange Programme.

## Specification

#### General

Cylinder Type	N-50
Invent Hazard Material (IMO/EU) classification	NA

#### Dimensions/Weight

Connection [Size/ Type]	W24.32mmx 1/14" RH Ext
Diameter [mm]	230
Gross Weight [kg]	92
Height [mm]	1690
Weight [kg]	11.5 Net

#### Performance data

Gas Capacity [m <sup>3</sup> ]	10.2
--------------------------------	------

### **Documents**

SDoC and MD for IHM

<u>Nitrogen</u>

# **Related products**

Accessories

# Colour green

Technical data

Physical properties

Connection [inch]	W24.32mmx 1/14" RH Ext
Filling pressure [bar]	up to 200bar
Purity	3.0 > 99.9%
Volume (I)	50



550160 WASHER ALU 10 PCS FOR OX REGULATOR

510002 REGULATOR 510 N2 PRESSURE 0-10 BAR

771713 REGULATOR 600 NITROGEN 0-200 BAR

510011 REGULATOR 510 N2 FLOW 0-1.3 L/MN

778147 TROLLEY F/1 40-50L GAS CYLINDER

Is frequently bought together with

905607 UNICOOL R-407C 52 KG REFRIGERANT 571356 ROCOR NB LIQUID 25 LTR 698720 AUTOTREAT - 25 LTR 905026 ACETYLENE A-40 FILLING 905034 OXYGEN O-40 FILLING

This page is printed from https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/gases/nitrogen/nitrogen-n-5030-filling/