Last updated: 30/04/2025 05:21:26

OXYGEN O-5 FILLING

Product group: **713** Product number: **905075**

In combination with Acetylene (C₂H₂), Oxygen (O₂) is used for gas cutting and welding. Small cylinders allows to access difficult accessible spaces. Backpack is available. This product is delivered in a Unitor cylinder as part of WSS global cylinder exchange program.

U n l T o R

Product information

Oxygen is a non-flammable gas but supports and accelerates combustion. Most materials burn with fierce intensity in oxygen. In Oxygen-enriched atmospheres, the potential fire risk increases and combustion is accelerated, even for materials that are normally not combustible. Avoid that oxygen comes in contact grease, fat and oil. Never use oxygen as substitute for compressed air.

Features

- Colourless, odourless and tasteless.
- It is approximately 1.1 times heavier than air
- Oxygen itself is non-flammable, but it supports combustion
- It can cause fire or explosion in combustible materials

Renefits

- Multi applications for ship maintenance like welding, cutting, brazing, soldering and heating.
- Suitable for AC-Ox Gas Distribution System
- For your safety, the product is delivered in a Unitor exchange cylinder complete with barcode and unique cylinder serial number.
- We trace and track all cylinders using our system to give you peace of mind.
- We offer global availability through our Global Exchange Programme.

Specification

General

Cylinder Type	O-5
Invent Hazard Material (IMO/EU) classification	C-21

Physical properties

Colour	Marine blue

Dimensions/Weight

Diameter [mm]	140
Gross Weight [kg]	13
Height [mm]	620
Weight [kg]	1.3 Net

Technical data

Connection [inch]	W21.8mmx 1/14" RH Ext
Filling pressure [bar]	up to 200bar
Purity	2.5 > 99.5%
. an ity	2.0 * 00.070
Values (I)	5
Volume (I)	o o

Performance data

Gas Capacity [m³]	1
-------------------	---

Documents

Understanding-Oxygen

SDoC and MD for IHM

Related products

Accessories

550160WASHER ALU 10 PCS FOR OX REGULATOR **510000**

REGULATOR 510 OX PRESSURE 0-10 BAR

Is frequently bought together with

905034

OXYGEN O-40 FILLING

905174 ARGON E-50 FILLING 905067 ACETYLENE A-5 FILLING 905026

ACETYLENE A-40 FILLING

905565

ARGON E-10 FILLING

This page is printed from

https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/gases/oxygen/oxygen-o-5-filling/products/gases-refrigerants-and-cylinders/gases/oxygen/oxygen-o-5-filling/products/gases-refrigerants-and-cylinders/gases/oxygen/oxygen-o-5-filling/products/gases-refrigerants-and-cylinders/gases/oxygen/oxygen-o-5-filling/products/gases-refrigerants-and-cylinders/gases/oxygen/oxygen-o-5-filling/products/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders/gases-refrigerants-and-cylinders-gases-gas