

Product group: **592** Product number: **905557**

A synthetic HFC refrigerant which is harmless to the ozone layer. The gas is used in a variety of maritime refrigeration applications such as air conditioning systems, reefer box cooling, engine control room AC and cargo cooling.



Product information

Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer
- Conforms to AHRI-700 purity standard

Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

Specification

General

Cylinder Type	Refr-56
GWP	1430
Invent Hazard Material (IMO/EU) classification	C-25
ODP	0

Physical properties

Colour	Light blue
--------	------------

Dimensions/Weight

Connection [Size/ Type]	OGA660
Diameter [mm]	254
Gross Weight [kg]	86 approx.
Height [mm]	1380
Weight [kg]	

Technical data

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

544932
REFRIGERANT CYL. VALVE ADAPTOR SET

513564
CYLINDER STAND

597757
CHARGING HOSE SET UCH-72 3X1.8M

Is frequently bought together with

905208
NITROGEN N-5030 FILLING

752154
REFRIGERATION HANDY TOOLS CASE

652522
REFRIGERANT RECOVERY PACKAGE F/220V

716142
REFRIGERANT LEAK DETECTOR UNIRX-1A

743466
DUCT AIR TREATMENT 2KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-134a/unicool-r-134a-57kg-refrigerant/>