

Last updated: 16/01/2026 21:16:51

# UNICOOL R-22 57 KG REFRIGERANT

Product group: **591** Product number: **905059**

A synthetic HCFC refrigerant with an Ozone Depleting Potential. The gas is used in a variety of maritime refrigeration applications for low, medium and high temperatures (-40 to +16° C). NOTE: the use of R-22 (virgin and reclaimed) is banned in the EU.



## Product information

### Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer

### Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

## Specification

### General

<b>Cylinder Type</b>	Refr-56
<b>GWP</b>	1810
<b>Invent Hazard Material (IMO/EU) classification</b>	A-3
<b>ODP</b>	0.049

### Physical properties

<b>Colour</b>	Green
---------------	-------

### Dimensions/Weight

<b>Connection [Size/ Type]</b>	CGA660
<b>Diameter [mm]</b>	254
<b>Gross Weight [kg]</b>	86 approx.
<b>Height [mm]</b>	1380
<b>Weight [kg]</b>	57 Net

### Performance data

<b>"Copper corrosion, DIN EN ISO 2160, 24 h/100°C"</b>	
--	--

## Documents

[SDoC and MD for IHM](#)

[SDoC and MD for IHM](#)

## Related products

### Accessories

**597757**  
CHARGING HOSE SET UCH-72 3X1.8M

**544932**  
REFRIGERANT CYL. VALVE ADAPTOR SET

**513564**  
CYLINDER STAND

Is frequently bought together with

**905208**  
NITROGEN N-5030 FILLING

**716142**  
REFRIGERANT LEAK DETECTOR UNIRX-1A

**752154**  
REFRIGERATION HANDY TOOLS CASE

**652522**  
REFRIGERANT RECOVERY PACKAGE F/220V

**743466**  
DUCT AIR TREATMENT 2KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-22/unicool-r-22-57-kg-refrigerant/>