

Product group: **591** Product number: **905059**

A synthetic HCFC refrigerant with an Ozone Depleting Potential. The gas is used in a variety of maritime refrigeration applications for low, medium and high temperatures (-40 to +16° C). NOTE: the use of R-22 (virgin and reclaimed) is banned in the EU.



Product information

Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer

Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

Specification

General

| | |
|--|---------|
| Cylinder Type | Refr-56 |
| GWP | 1810 |
| Invent Hazard Material (IMO/EU) classification | A-3 |
| ODP | 0.049 |

Physical properties

| | |
|--------|-------|
| Colour | Green |
|--------|-------|

Dimensions/Weight

| | |
|-------------------------|------------|
| Connection [Size/ Type] | CGA660 |
| Diameter [mm] | 254 |
| Gross Weight [kg] | 86 approx. |
| Height [mm] | 1380 |
| Weight [kg] | |

Documents

[SDoC and MD for IHM](#)

[SDoC and MD for IHM](#)

Related products

Accessories

544932
REFRIGERANT CYL. VALVE ADAPTOR SET

513564
CYLINDER STAND

597757
CHARGING HOSE SET UCH-72 3X1.8M

Is frequently bought together with

905208
NITROGEN N-5030 FILLING

752154
REFRIGERATION HANDY TOOLS CASE

652522
REFRIGERANT RECOVERY PACKAGE F/220V

716142
REFRIGERANT LEAK DETECTOR UNIRX-1A

743466
DUCT AIR TREATMENT 2KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-22/unicool-r-22-57-kg-refrigerant/>