

Product group: 591 Product number: 905059

A synthetic HCFC refrigerant with an Ozone Depleting Potential. The gas is used in a variety of maritime refrigeration applications for low, medium and high temperatures (-40 to +16° C). NOTE: the use of R-22 (virgin and reclaimed) is banned in the EU.



Product information

Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer

Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

Specification

General

Cylinder Type	Refr-56
GWP	1810
Invent Hazard Material (IMO/EU) classification	A-3
ODP	0.049

Physical properties

Colour	Green
--------	-------

Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	254
Gross Weight [kg]	86 approx.
Height [mm]	1380
Weight [kg]	

Documents

[SDoC and MD for IHM](#)

[SDoC and MD for IHM](#)

Related products

Accessories

- 597757
CHARGING HOSE SET UCH-72 3X1.8M
- 544932
REFRIGERANT CYL. VALVE ADAPTOR SET
- 513564
CYLINDER STAND

Is frequently bought together with

- 905208
NITROGEN N-5030 FILLING
- 716142
REFRIGERANT LEAK DETECTOR UNIRX-1A
- 752154
REFRIGERATION HANDY TOOLS CASE
- 652522
REFRIGERANT RECOVERY PACKAGE F/220V
- 743466
DUCT AIR TREATMENT 2KG