Last updated: 02/07/2025 01:00:55



# UNICOOL R-404A 45 KG REFRIGERANT

Product group: **590** Product number: **905606** 

A synthetic HFC refrigerant which is harmless to the ozone layer. The gas is used in a variety of maritime refrigeration applications such as low and medium temperature applications (Evaporating temperatures of -45 to +8° C).



## **Product information**

#### Features

- · All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine virgin refrigerant from approved producer
- Conforms to AHRI-700 purity standard
- Areplacement option for R-502 and R-22
- Most suitable for new systems

#### Benefits

- Worldwide compliance
- Assured quality
- · Refillable cylinders

#### **Specification**

#### General

Cylinder Type	Refr-56
GWP	3922
Invent Hazard Material (IMO/EU) classification	C-25
ODP	0

#### Physical properties

Colour	Pastel Orange
--------	---------------

## Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	254
Gross Weight [kg]	74 approx.
Height [mm]	1380
Weight [kg]	45 Net

## Technical data

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)

## Documents

SDoC and MD for IHM

### **Related products**

Accessories

597757

CHARGING HOSE SET UCH-72 3X1.8M

544932

REFRIGERANT CYL. VALVE ADAPTOR SET

513564

CYLINDER STAND

Is frequently bought together with

905208

NITROGEN N-5030 FILLING

716142

REFRIGERANT LEAK DETECTOR UNIRX-1A

752154

REFRIGERATION HANDY TOOLS CASE

652522
REFRIGERANT RECOVERY PACKAGE F/220V
743466
DUCT AIR TREATMENT 2KG

This page is printed from

 $https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-404a/unicool-r-404a-45-kg-refrigerant-for-non\_eu-export-only/linear-linea$