

Product group: 594 Product number: 905624

A synthetic HFC refrigerant which is harmless to the ozone layer. The gas is used in a variety of maritime refrigeration applications such as high and medium temperature applications (evaporating temperatures of -25 to +15° C).

Product information

Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer
- Conforms to AHRI-700 purity standardSuitable for new systems and retrofits

Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

Specification

General

Cylinder Type	Refr-12
GWP	1774
Invent Hazard Material (IMO/EU) classification	C-25
ODP	0

Physical properties

Colour

Orange brow n

Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	229
Gross Weight [kg]	20 approx.
Height [mm]	506
Weight [kg]	

Documents

SDoC and MD for IHM

Related products

Accessories

597757 CHARGING HOSE SET UCH-72 3X1.8M 544932 REFRIGERANT CYL. VALVE ADAPTOR SET

Is frequently bought together with

905232 NITROGEN N-1030 FILLING 716142 REFRIGERANT LEAK DETECTOR UNIRX-1A 752154 REFRIGERATION HANDY TOOLS CASE 652522 REFRIGERANT RECOVERY PACKAGE F/220V 743466 DUCT AIR TREATMENT 2KG

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-407c/uniccol-r-407-c-11-kg-refrigerant/



Technical data

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)