

Last updated: 16/02/2024 06:10:05

UNICOOL R-410A 45 KG REFRIGERANT

Product group: **594** Product number: **905608**

A synthetic HFC refrigerant which is harmless to the ozone layer. The gas is used in a variety of maritime refrigeration applications such as low, medium and high temperature applications (evaporating temperatures of -45 to +8° C).

Product information

Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer
- Conforms to AHRI-700 purity standard
- For new systems only

Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

Specification

General

Cylinder Type	Refr-56
GWP	2090
Invent Hazard Material (IMO/EU) classification	C-25
ODP	0

Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	254
Gross Weight [kg]	74 approx.
Height [mm]	1380
Weight [kg]	45 Net

Documents

SDoC and MD for IHM

Related products

Accessories 597757 CHARGING HOSE SET UCH-72 3X1.8M 544932 REFRIGERANT CYL. VALVE ADAPTOR SET 513564 CYLINDER STAND

Is frequently bought together with

Physical properties

Colour	Light Pink

Technical data

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)





905208 NITROGEN N-5030 FILLING 716142 REFRIGERANT LEAK DETECTOR UNIRX-1A 752154 REFRIGERATION HANDY TOOLS CASE 652522 REFRIGERANT RECOVERY PACKAGE F/220V 743466 DUCT AIR TREATMENT 2KG

This page is printed from

https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-410a/unicool-r-410a-45-kg-refrigerant/refrigerants/refrig