

Product group: **594** Product number: **905608**

A synthetic HFC refrigerant which is harmless to the ozone layer. The gas is used in a variety of maritime refrigeration applications such as low, medium and high temperature applications (evaporating temperatures of -45 to +8° C).



## Product information

### Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer
- Conforms to ARI-700 purity standard
- For new systems only

### Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

## Specification

### General

<b>Cylinder Type</b>	Refr-56
<b>GWP</b>	2090
<b>Invent Hazard Material (IMO/EU) classification</b>	C-25
<b>ODP</b>	0

### Dimensions/Weight

<b>Connection [Size/ Type]</b>	CGA660
<b>Diameter [mm]</b>	254
<b>Gross Weight [kg]</b>	74 approx.
<b>Height [mm]</b>	1380
<b>Weight [kg]</b>	45 Net

### Physical properties

<b>Colour</b>	Light Pink
---------------	------------

### Technical data

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)

## Documents

[SDoC and MD for IHM](#)

## Related products

### Accessories

**597757**  
CHARGING HOSE SET UCH-72 3X1.8M

**544932**  
REFRIGERANT CYL. VALVE ADAPTOR SET

**513564**  
CYLINDER STAND

### Is frequently bought together with

**905208**  
NITROGEN N-5030 FILLING

**716142**  
REFRIGERANT LEAK DETECTOR UNIRX-1A

**752154**  
REFRIGERATION HANDY TOOLS CASE

**652522**  
REFRIGERANT RECOVERY PACKAGE F/220V

**743466**  
DUCT AIR TREATMENT 2KG

**This page is printed from:**

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-410a/unicool-r-410a-45-kg-refrigerant/>

