

Product group: **594** Product number: **905627** 

A synthetic HFC refrigerant which is harmless to the ozone layer. The gas is used in a variety of maritime refrigeration applications such as low, medium and high temperature applications (evaporating temperatures of -45 to  $+8^{\circ}$  C).

# 1410A 95K

#### **Product information**

#### Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer
- Conforms to AHRI-700 purity standard
- · For new systems only

#### **Benefits**

- Worldwide compliance
- Assured quality
- Refillable cylinders

## **Specification**

#### General

Cylinder Type	Refr-12
GWP	2090
Invent Hazard Material (IMO/EJ) classification	C-25
ODP	0

### Physical properties

Colour	Light Pink
--------	------------

#### Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	229
Gross Weight [kg]	18 approx.
Height [mm]	506
Weight [kg]	

#### Technical data

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)

#### **Documents**

SDoC and MD for IHM

# Related products

#### Accessories

597757

CHARGING HOSE SET UCH-72 3X1.8M

544932

REFRIGERANT CYL. VALVE ADAPTOR SET

# Is frequently bought together with

905232

NITROGEN N-1030 FILLING

716142

REFRIGERANT LEAK DETECTOR UNIRX-1A

752154

REFRIGERATION HANDY TOOLS CASE

652522

REFRIGERANT RECOVERY PACKAGE F/220V

743466

DUCT AIR TREATMENT 2KG

#### This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-410a/unicool-r-410a-9.5-kg-refrigerant/refrigerants/refri