

Product group: **594** Product number: **905627**

A synthetic HFC refrigerant which is harmless to the ozone layer. The gas is used in a variety of maritime refrigeration applications such as low, medium and high temperature applications (evaporating temperatures of -45 to +8° C).



Product information

Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer
- Conforms to AHRI-700 purity standard
- For new systems only

Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

Specification

General

Cylinder Type	Refr-12
GWP	2090
Invent Hazard Material (IMO/EU) classification	C-25
ODP	0

Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	229
Gross Weight [kg]	18 approx.
Height [mm]	506
Weight [kg]	

Physical properties

Colour	Light Pink
--------	------------

Technical data

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

544932
REFRIGERANT CYL. VALVE ADAPTOR SET
597757
CHARGING HOSE SET UCH-72 3X1.8M

Is frequently bought together with

905232
NITROGEN N-1030 FILLING
752154
REFRIGERATION HANDY TOOLS CASE
652522
REFRIGERANT RECOVERY PACKAGE F/220V
716142
REFRIGERANT LEAK DETECTOR UNIRX-1A
743466
DUCT AIR TREATMENT 2KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-410a/unicool-r-410a-9.5-kg-refrigerant>