

Product group: 594 Product number: 905627

A synthetic HFC refrigerant which is harmless to the ozone layer. The gas is used in a variety of maritime refrigeration applications such as low, medium and high temperature applications (evaporating temperatures of -45 to +8° C).

Product information

Features

- . All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage •
- Content is 100% genuine refrigerant from approved producer
- Conforms to AHRI-700 purity standard • •
- For new systems only

Benefits

- Worldwide compliance •
- Assured quality
- Refillable cylinders

Specification

General

Cylinder Type	Refr-12
GWP	2090
Invent Hazard Material (IMO/EU) classification	C-25
ODP	0

Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	229
Gross Weight [kg]	18 approx.
Height [mm]	506
Weight [kg]	

Technical data

Physical properties

Colour

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)

Light Pink

Documents

SDoC and MD for IHM

Related products

Accessories

544932 REFRIGERANT CYL. VALVE ADAPTOR SET 597757 CHARGING HOSE SET UCH-72 3X1.8M

Is frequently bought together with

905232 NITROGEN N-1030 FILLING 752154 REFRIGERATION HANDY TOOLS CASE 652522 REFRIGERANT RECOVERY PACKAGE F/220V 716142 REFRIGERANT LEAK DETECTOR UNIRX-1A 743466 DUCT AIR TREATMENT 2KG

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-410a/unicool-r-410a-9.5-kg-refrigerant

