

Product group: 593 Product number: 905637

Environmentally acceptable HFC solution for replacing ozone depleting R-22 refrigerants in existing refrigeration systems as low, medium and high temperature applications (evaporating temperatures of -35 to +25° C).
This is a WSS preferred retrofit solution.



Product information

Features

- Quality Guaranteed - purity and moisture content are guaranteed as per AHRI Standard 700.
- Global Availability - Products are available in WSS global network with the same specification and quality.
- Compatibility - R-417A is compatible with both POE and mineral oil in existing R-22 system.
- Recommended for existing R-22 system.

Benefits

- Safety and Authenticity - Refrigerants delivered under the WSS Global Cylinder Ex-change program are fully traceable, safe, authentic, and thus eliminate the risks of receiving illegal or counterfeit refrigerants.
- Cost Effective- Reduce downtime and Cost as the refrigerant is compatible with mineral oil in existing R-22 systems.
- Worldwide Compliance - This low GWP refrigerant solution enables ship owners to stay compliant with all international regulations.

Specification

General

Cylinder Type	Refr-56
GWP	2346
Invent Hazard Material (IMO/EU) classification	C-25
ODP	0

Physical properties

Colour	Green
--------	-------

Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	254
Gross Weight [kg]	80 approx.
Height [mm]	1380
Weight [kg]	

Technical data

ODP = Ozone Depletion Potential
GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

- 597757
CHARGING HOSE SET UCH-72 3X1.8M
- 544932
REFRIGERANT CYL. VALVE ADAPTOR SET
- 513564
CYLINDER STAND

Is frequently bought together with

- 905208
NITROGEN N-5030 FILLING
- 716142
REFRIGERANT LEAK DETECTOR UNIRX-1A
- 752154
REFRIGERATION HANDY TOOLS CASE
- 652522
REFRIGERANT RECOVERY PACKAGE F/220V
- 743466
DUCT AIR TREATMENT 2KG