

Product group: 592 Product number: 905770

A new generation of HFO/HFC blend refrigerant which is non-flammable and harmless to the ozone layer. Excellent low GWP refrigerant for medium temperature applications. Suitable for both new installation and existing R-134a system.



Product information

Features

- Non-flammable with a safety classification of A1
- Quality Guaranteed - purity and moisture content are guaranteed as per AHRI Standard 700.
- Global Availability - Products are available in WSS global network with the same specification and quality.
- No Performance Drop - it provides similar capacity to R-134a in medium temp. application.
- Suitable for new installation and retrofit.

Benefits

- Safety and Authenticity - Refrigerants delivered under the WSS Global Cylinder Ex-change program are fully traceable, safe, authentic, and thus eliminate the risks of receiving illegal or counterfeit refrigerants.
- Cost Effective- Reduce downtime and cost as the refrigerant is compatible with existing R-134a systems.
- Worldwide Compliance - This low GWP refrigerant solution enables ship owners to stay compliant with all international regulations.

Specification

General

GWP	631
Invent Hazard Material (IMO/EU) classification	C-25
ODP	0

Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	254
Gross Weight [kg]	79 approx.
Height [mm]	1380
Weight [kg]	

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

711480
DIGI-MANIFOLD SET (4-WAY)

544932
REFRIGERANT CYL. VALVE ADAPTOR SET

513564
CYLINDER STAND

597757
CHARGING HOSE SET UCH-72 3X1.8M

This page is printed from:
<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/unicool-r-513a-50kg-refrigerant/>