

Product group: 716 Product number: 510004

A general purpose brass regulator for CO₂ (Carbon dioxide)

Product information



This product supersedes product no: 656199

For use with Unitor CO2 cylinders for potable water treatment, in shielding gas applications or for beverage dispensing.

Apart from replacing damaged or faulty gauges, repairs should never be attempted on gas regulators. Faulty, old or corroded regulators should be replaced. Internal seals and membranes will deteriorate with time, and as a rule gas regulators should be replaced with maximum 5 years intervals.

Features

- Built according to international norm EN ISO 2503
- Single-stage
- Inlet connection: CGA320 / 0.825"-14 NGO-RH-Int
- Outlet connection: 3/8" BSP RH Ext
- Max inlet pressure: 200 bar
- Outlet pressure range: 0 - 10 bar
- Comes with a pressure relief valve

Benefits

- Reduces cylinder pressure to safe working pressure.
- Suitable for connection with Unitor C-9 and C-27 cylinders.
- Inlet gauge to inform available pressure in the cylinder.

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Connection [Size/ Type]	CGA 320 (inlet)
Depth[mm]	100
Length [mm]	160
Width [mm]	115

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

905619
CARBON DIOXIDE C-9 FILLING
905695
CARBON DIOXIDE C-27 FILLING

Is frequently bought together with

551176
COLLET BODY 2,4MM FOR TIG-TORCH
575613
AQUABREAK PX 25 LTR
571752
NATURAL HANDCLEANER 4X5 LTR
607826
AQUATUFF 25 LTR
568568
BACTERIA COUNT TEST (10 PCS)

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/regulators/regulators-for-argonco2/regulator-510-co2-for-c-9-and-c-27-cylinder/>