

Last updated: 30/04/2025 05:21:03

REGULATOR 510 CO2 FOR C-9 AND C-27 CYLINDER

Product group: **716** Product number: **510004** A general purpose brass regulator for CO₂ (Carbon dioxide)

Product information

This product supersedes product no: 656199

For use with Unitor CO2 cylinders for potable water treatment, in shielding gas applications or for beverage dispensing.

Apart from replacing damaged or faulty gauges, repairs should never be attempted on gas regulators. Faulty, old or corroded regulators should be replaced. Internal seals and membranes will deteriorate with time, and as a rule gas regulators should be replaced with maximum 5 years intervals.

Features

- Built according to international norm EN ISO 2503
- Single-stage
- Inlet connection: CGA320 / 0.825"-14 NGO-RH-Int
- Oultet connection: 3/8" BSP RH Ext
- Maxinlet pressure: 200 bar
- Outlet pressure range: 0 10 bar
- Comes with a pressure relief valve

Benefits

- Reduces cylinder pressure to safe working pressure.
- Suitable for connection with Unitor C-9 and C-27 cylinders.
- Inlet gauge to inform available pressure in the cylinder.

Specification

General

NA

Dimensions/Weight

Connection [Size/ Type]	CGA 320 (inlet)
Depth[mm]	100
Length [mm]	160
Width [mm]	115

Documents

SDoC and MD for IHM

Related products

Is accessory to 905619 CARBON DIOXIDE C-9 FILLING 905695 CARBON DIOXIDE C-27 FILLING

Is frequently bought together with 568568 BACTERIA COUNT TEST (10 PCS) 575613 AQUABREAK PX 25 LTR 607826 AQUATUFF 25 LTR 571752 NATURAL HANDCLEANER 4X5 LTR 551176 COLLET BODY 2,4MM FOR TIG-TORCH





This page is printed from

https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/regulators/regulators-for-argonco2/regulator-510-co2-for-c-9-and-c-27-cylinder/