

Product group: 716      Product number: 510004

A general purpose brass regulator for CO<sub>2</sub> (Carbon dioxide)

Product information



This product supersedes product no: 656199

For use with Unitor CO2 cylinders for potable water treatment, in shielding gas applications or for beverage dispensing.

Apart from replacing damaged or faulty gauges, repairs should never be attempted on gas regulators. Faulty, old or corroded regulators should be replaced. Internal seals and membranes will deteriorate with time, and as a rule gas regulators should be replaced with maximum 5 years intervals.

Features

- Built according to international norm EN ISO 2503
- Single-stage
- Inlet connection: CGA320 / 0.825"-14 NGO-RH-Int
- Outlet connection: 3/8" BSP RH Ext
- Max inlet pressure: 200 bar
- Outlet pressure range: 0 - 10 bar
- Comes with a pressure relief valve

Benefits

- Reduces cylinder pressure to safe working pressure.
- Suitable for connection with Unitor C-9 and C-27 cylinders.
- Inlet gauge to inform available pressure in the cylinder.

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Connection [Size/ Type]	CGA 320 (inlet)
Depth[mm]	100
Length [mm]	160
Width [mm]	115

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

905619  
CARBON DIOXIDE C-9 FILLING  
905695  
CARBON DIOXIDE C-27 FILLING

Is frequently bought together with

568568  
BACTERIA COUNT TEST (10 PCS)  
575613  
AQUABREAK PX 25 LTR  
607826  
AQUATUFF 25 LTR  
571752  
NATURAL HANDCLEANER 4X5 LTR  
551176  
COLLET BODY 2,4MM FOR TIG-TORCH

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/regulators/regulators-for-argonco2/regulator-510-co2-for-c-9-and-c-27-cylinder/>