

REGULATOR F/SCOTTY VI AND 4COMP

Product group: **718** Product number: **620013**

Regulator fitting on the Minimix 34 and 58 cylinder for constant flow.



Product information

Apart from replacing damaged or faulty gauges, repairs should never be attempted on gas regulators. Faulty, old or corroded regulators should be replaced. Internal seals and membranes will deteriorate with time, and as a rule gas regulators should be replaced with maximum 5 years intervals.

Features

- Regulator for Minimix 34 and 58 cylinder; also for Scotty VI cylinder
- Fixed flow setting; 0.5 l/min
- Outlet connection 3/16" hose
- Small length of hose is included

Benefits

- constant flow

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Connection [Size/ Type]	CGA C-10 = 5/8"- 18 UNF
-------------------------	-------------------------

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

741306	4-MIX 50 CO 25 H2S 50LEL CH4 18 OX	758722	4-MIX 100 CO 15 H2S 50LEL CH4 18 OX
620138	HYDROGEN SULPHIDE/N2 25 PPM (S 58)	734772	4-MIX 250 CO 15 H2S 50LEL CH4 18 OX
778175	4-MIX 50 CO 25 H2S 50LEL CH4 12 OX	742951	4-MIX 100 CO 15 H2S 2.2% CH4 18 OX
782161	AMMONIA 50 PPM IN AIR (SCOTTY 58)		

Is frequently bought together with

183418	FLEXIBLE HOSE 30CM 3/8IN	191692	40 USH SOCKET 1/2" HOSE
150150	UWI-150TP WELDING INVERTER IN CASE		
175273	WELD.GOGGLES W/LIFT-FRONT		
191882	30 UPM PLUG 3/8" MALE BSP.T		

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/regulators/regulators-for-spangas/regulator-fscotty-vi-and-4comp/>