

Product group: 718 Product number: 742951

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas



Product information

Gas Composition:

- Methane (CH4) - 2.2% (44% LEL)
- Oxygen (O2) - 18%
- Hydrogen Sulfide (H2S) - 15ppm
- Carbon Monoxide (CO) - 100ppm
- Nitrogen (N2) - balance

Used with regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Minimix 34
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	76
Height [mm]	289

Technical data

Shelf life [months]	24
Volume (l)	0.9

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

620013
REGULATOR F/SCOTTY M AND 4COMP

Is frequently bought together with

- 698720
AUTOTREAT - 25 LTR
- 765018
ENVIROCLEAN 25 LTR
- 774828
CONDENSATE CONTROL 25 LTR
- 905034
OXYGEN O-40 FILLING
- 571356
ROCOR NB LIQUID 25 LTR

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/4-nix-100-co-15-h2s-2.2-ch4-18-ox/>

