

Product group: **718**      Product number: **758722**

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas



Product information

Gas Composition:

- Methane (CH4) - 2.5% (50% LEL)
- Oxygen (O2) - 18%
- Hydrogen Sulfide (H2S) - 15ppm
- Carbon Monoxide (CO) - 100ppm
- Nitrogen (N2) - balance

Used with regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Mnimix 34
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	76
Height [mm]	289

Technical data

Shelf life [months]	24
Volume (l)	0.9

Documents

[Span-Gases](#)

[SDoC and MD for IHM](#)

Related products

Accessories

**620013**  
REGULATOR F/SCOTTY M AND 4COMP

Is frequently bought together with

**510001**  
REGULATOR 510 AC PRESSURE 0-1.5 BAR

**510000**  
REGULATOR 510 OX PRESSURE 0-10 BAR

**150150**  
UWM-150 TP WELDING INVERTER IN CASE (1P 230V)

**546036**  
COUPLING KIT ERGO 3000

**607441**  
SQUEEGEE W/WOODEN HANDLE

**This page is printed from:**

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/4-mix-100-co-15-h2s-50lel-ch4-18-ox/>