

Product group: 718 Product number: 778175

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas



Product information

Gas Composition:

- Methane (CH4) - 2.5% (50% LEL)
- Oxygen (O2) - 12%
- Hydrogen Sulfide (H2S) - 25ppm
- Carbon Monoxide (CO) - 50ppm
- Nitrogen (N2) - balance

Used with regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Minimix 34
Invent Hazard Material (IMO/IU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	76
Height [mm]	289

Technical data

Shelf life [months]	24
Volume (l)	0.9

Documents

[SDoC and MD for IHM](#)

[media](#)

Related products

Accessories

620013
REGULATOR F/SCOTTY M AND 4COMP

Is frequently bought together with

- 619973
MNIMX PURE NITROGEN
- 619932
MNIMX 17 ISOBUTANE 0.9%AIR
- 620138
MNIMX 58 HYDROGEN SULPHIDE(H2S) 25 PPM IN NITROGEN
- 620039
MNIMX17 CARBON MONOXIDE 60PPM
- 741306
MNIMX 34 4-MX 50 CO 25 H2S 50LEL CH4 18 OX

