

Product group: 718      Product number: 782161

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas

Product information

This product supersedes product no: L00654, L16234

Gas Composition:

Ammonia (NH3) - 50ppm  
Air - balance

Used with Regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Mnimix 58
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	76
Height [mm]	289

Technical data

Shelf life [months]	24
Volume (l)	0.9

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

620013  
REGULATOR F/SCOTTY M AND 4COMP

Is frequently bought together with

- 778175  
MNIMIX34 4-MX50 CO 25 H2S 50LEL CH4 12 OX
- 905026  
ACETYLENE A-40 FILLING
- 905034  
OXYGEN O-40 FILLING
- 905606  
UNICOOL R-404A 45 KG REFRIGERANT
- 620138  
MNIMIX58 HYDROGEN SULPHIDE(H2S) 25 PPM IN NITROGEN

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/ammonia-50-ppm-in-air--s-58/>