

Product group: 718 Product number: 620138

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas



Product information

This product supersedes product no: L38348

Gas Composition:

Hydrogen Sulfide (H2S) - 25ppm
Nitrogen (N2) - balance

Used with regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Mnimix 58
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	89
Height [mm]	343

Technical data

Shelf life [months]	24
Volume (l)	1.7

Documents

[Span-Gases](#)

[SDoC and MD for IHM](#)

Related products

Accessories

620013
REGULATOR F/SCOTTY M AND 4COMP

Is frequently bought together with

620039
MINIMX17 CARBON MONOXIDE 60PPM

619965
MINIMX 17 2.5% METHANE-AIR

778175
MINIMX34 4-MX50 CO 25 H2S 50LEL CH4 12 OX

619973
MINIMX PURE NITROGEN

619932
MINIMX 17 ISOBUTANE 0.9%AIR

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/hydrogen-sulphiden2-25-ppm-s-58/>