

Last updated: 30/04/2025 05:23:18

# MINIMIX 58 HYDROGEN SULPHIDE(H2S) 25 PPM IN NITROGEN

Product group: 718      Product number: 620138

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas



## Product information

This product supersedes product no: L38348

Gas Composition:

Hydrogen Sulfide (H2S) - 25ppm  
Nitrogen (N2) - balance

Used with regulator 620013

### Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

### Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

## Specification

### General

Cylinder Type	Minimix 58
Invent Hazard Material (IMO/IU) classification	NA

### Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	89
Height [mm]	343

### Technical data

Shelf life [months]	24
Volume (l)	1.7

## Documents

[SDoC and MD for IHM](#)

[Span-Gases](#)

## Related products

### Accessories

620013  
REGULATOR F/SCOTTY M AND 4COMP

Is frequently bought together with

**619965**  
MINIMX 17 2.5% METHANE-AIR

**778175**  
MINIMX 34 4-MX 50 CO 25 H2S 50LEL CH4 12 OX

**619973**  
MINIMX PURE NITROGEN

**619932**  
MINIMX 17 ISOBUTANE 0.9%AIR