

### Product group: 718 Product number: 630077

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas

# Product information

Gas Composition:

Iso-butane (iC4H10) - 0.9% (50% LEL) Oxygen (O2) - 12% Hydrogen Sulfide (H2S) - 25ppm Carbon Monoxide (CO) - 50ppm Nitrogen (N2) - balance

### Used with regulator 620013

#### Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

#### Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

### **Specification**

### General

Cylinder Type	Minimix 34
Invent Hazard Material (IMO/EU) classification	NA

## Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	76
Height [mm]	289

### Technical data

Shelf life [months]	24
Volume (I)	0.9

#### **Documents**

<u>media</u>

<u>media</u>

## **Related products**

Accessories 620013 REGULATOR F/SCOTTY VI AND 4COMP

### This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/mininix-34-4-mix-50-co-25-h2s-50lel-i-c4h10-12-ox/

