

Product group: 718 Product number: 630075

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas

Product information

Gas Composition:

Oxygen - 12% Nitrogen (N2) - balance

Used with Regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGAC-10 connection
- Each cylinder delivered with a Certificate of AnalysisGuaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Minimix 34
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	76
Height [mm]	289

Technical data

Volume (I) 0.9	

Documents

SDoC and MD for IHM

<u>media</u>

Related products

Accessories 620013 REGULATOR F/SCOTTY VI AND 4COMP

This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/minimx-34-o2-12-in-88-n2/

