

BUTANE IN AIR 35% LEL

Product group: **718** Product number: **588962**

Span gases are used for calibration and bump testing of gas detection equipment.



Product information

The cylinder is a 200 bar cylinder made to the double standard (ISO/USDOT) and with TPED/UN/USDOT approval.

Features

- Refillable SG10 cylinder
- Composition: 0.63% butane (C₄H₁₀), balance is air. Equals 35% L.E.L. mixture

Benefits

- This product is delivered in a Unitor cylinder with its barcode and unique cylinder serial number
- All cylinders are traced and tracked using the UniTrak system

Specification

General

Cylinder Type	SG-10
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	W24.32mm x 1/14" Ext
Gross Weight [kg]	21

Technical data

Shelf life [months]	36
----------------------------	----

Documents

[Span-Gases](#)

[SDoC and MD for IHM](#)

Related products

Accessories

- 510003** REGULATOR 510 N2 PRESSURE 0 -1 BAR
- 510011** REGULATOR 510 N2 FLOW 0-1.3 L/MIN

Is frequently bought together with

- 905034** OXYGEN O-40 FILLING
- 905026** ACETYLENE A-40 FILLING
- 905601** NITROGEN N-5050 FILLING
- 510011** REGULATOR 510 N2 FLOW 0-1.3 L/MIN
- 905602** NITROGEN N-1050 FILLING

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/lel-mixtures/butane-in-air-35-lel/>