

Last updated: 09/03/2026 11:36:57

AQUABREAK PX 25 LTR

Product group: **651** Product number: **575613**

Unitor™ Aquabreak PX is a multipurpose cleaning and degreasing agent. It is low-toxic, non-caustic, free of hydrocarbon solvents and biodegradable. It has excellent dispersant property.



Product information

Unitor™ Aquabreak PX removes effectively dirt and oily matters without the use of solvents and caustic based cleaners. The surfactant formulation with complex binders has an excellent cleaning efficiency. Unitor™ Aquabreak PX is NSF approved so it can be used to clean food serving areas and food stations.

Optimal for use in the following applications:

- Good for use in galleys and on decks
- Engine room cleaner
- Suitable for cargo tank cleaning
- Suitable for cleaning of soiled textiles as rugs, covers, mats, overalls etc.
- Effectively cleans fiberglass boats.

Features

- Multi purpose water based degreaser
- Highly concentrated
- Biodegradable, low toxic and non-caustic
- Safe on all materials

Benefits

- Has multi-functional applications so you can minimise the number of cleaners used onboard.
- Safe to use and your safety is always our priority.
- Minimise the risk of damaging surfaces

Specification

General

Invent Hazard Material (IMO/IU) classification	C-49
---	------

Physical properties

Appearance	Pale yellow
Density [g/ml]	1,020 - 1,035
Form	Liquid
pH	12

Approvals

Approved by NSF

Nordic Swan eco-labelled.

This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

IMO approved and listed in Annex 10 of the MEPC.2/ Circular

Approved by Marinfloc AB for use in engine rooms

[Aquabreak-approval-drink-water-offshore](#)

Documents

[Direct access to the Environmental Product Declaration \(EPD\) for this product](#)

[SDoC and MD for IHM](#)

Directions for use

General Cleaning

Unitor™ Aquabreak PX™ can be used for all types of cleaning and degreasing, and it can be applied by brush, hand spray.

It is recommended to test different concentrations on a small area to find the optimal effect on the contaminated surface. Depending on the amount and type soil to be

removed, common dosage for light contamination is about 1-5%, for heavy contamination up to 20%.

For safe handling and optimal dilution we recommend the use of UNITOR 4 CHEMICALS DILUTION STATION (PN:778862**)**

Unitor™ Aquabreak PX™ can be applied on vertical surfaces by adding Unitor™ Foam Agent™ for increasing the resident time.

Tank Cleaning

Direct injection method with tank washing machines:

Use a dose rate of 0.5-5 litres per ton wash water (0.05-0.5%).

Recirculation method:

Use a dose rate of 0.5-7 litres per ton wash water (0.05-0.7%).

Spot cleaning: Hand sprayed neat or diluted up to 1-5 parts with water. Leave solution for about 20-30 minutes before washing off, but make sure the surface remains wet.

For problem deposits, please consult the Unitor™ Tank Cleaning Manual.

Unitor™ Aquabreak PX™ can be used on the majority of tank coating materials, painted or lacquered surfaces, light metals, plastics and textiles.

Related products

Accessories

614537

FOAM- AGENT 3X5 LTR

Is accessory to

778993

OILSPILL MARPOL KIT 12 BARREL(2 PALLETS)

778914

OILSPILL MARPOL KIT 7 BARREL(2 PALLETS)

Is consumable by

778862

UNITOR 4 CHEMICALS DILUTION STATION

778922

OILSPILL MARPOL KIT1 BARREL(1 PALLET)

737189

CHEM. CLEAN. UNIT W/HEATING, COATED

2009029

NAVADAN ULTIMATE KIT

2009025

NAVADAN PANAMAX KIT

2009026

NAVADAN ESSENTIAL KIT

Is frequently bought together with

2009034

NAVADAN PROTECTION KIT

765018

ENVIROCLEAN 25 LTR

571321

ULTRACLEAN GO 25 LTR

571646

DESCALEX 25 KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/aquabreak-px-25-ltr/>