

Last updated: 18/06/2025 09:44:39

# AQUABREAK PX 25 LTR

Product group: 651      Product number: 575613

Unitor™ Aquabreak PX™ is a multipurpose cleaning and degreasing agent. It is low-toxic, non-caustic, free of hydrocarbon solvents and biodegradable. It has excellent dispersant property.



## Product information

Unitor™ Aquabreak PX™ removes effectively dirt and oily matters without the use of solvents and caustic based cleaners. The surfactant formulation with complex binders has an excellent cleaning efficiency. Unitor™ Aquabreak PX™ is NSF approved so it can be used to clean food serving areas and food stations.

Optimal for use in the following applications:

- Good for use in galleys and on decks
- Engine room cleaner
- Suitable for cargo tank cleaning
- Suitable for cleaning of soiled textiles as rugs, covers, mats, overalls etc.
- Effectively cleans fiberglass boats.

### Features

- Multi purpose water based degreaser
- Highly concentrated
- Biodegradable, low toxic and non-caustic
- Safe on all materials

### Benefits

- Has multi-functional applications so you can minimise the number of cleaners used onboard.
- Safe to use and your safety is always our priority.
- Minimise the risk of damaging surfaces

## Specification

### General

Invent Hazard Material (IMO/IU) classification	C-49
--	------

### Physical properties

Appearance	Pale yellow
Density [g/ml]	1,020 - 1,035
Form	Liquid
pH	12

## Approvals

Approved by NSF

Nordic Swan eco-labelled.

This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

IMO approved and listed in Annex 10 of the MEPC.2/ Circular

Approved by Marinfloc AB for use in engine rooms

[Aquabreak-approval-drink-water-offshore](#)

## Documents

[SDoC and MD for IHM](#)

## Directions for use

### General Cleaning

Unitor™ Aquabreak PX™ can be used for all types of cleaning and degreasing, and it can be applied by brush, hand spray.

It is recommended to test different concentrations on a small area to find the optimal effect on the contaminated surface. Depending on the amount and type soil to be removed, common dosage for light contamination is about 1-5%, for heavy contamination up to 20%.

For safe handling and optimal dilution we recommend the use of UNITOR 4 CHEMICALS DILUTION STATION (PN:778862\*\*) \*\*

Unitor™ Aquabreak PX™ can be applied on vertical surfaces by adding Unitor™ Foam Agent™ for increasing the resident time.

Tank Cleaning

Direct injection method with tank washing machines:

Use a dose rate of 0.5-5 litres per ton wash water (0.05-0.5%).

Recirculation method:

Use a dose rate of 0.5-7 litres per ton wash water (0.05-0.7%).

**Spot cleaning:** Hand sprayed neat or diluted up to 1-5 parts with water. Leave solution for about 20-30 minutes before washing off, but make sure the surface remains wet.

For problem deposits, please consult the Unitor™ Tank Cleaning Manual.

Unitor™ Aquabreak PX™ can be used on the majority of tank coating materials, painted or lacquered surfaces, light metals, plastics and textiles.

Related products

Accessories

614537  
FOAM- AGENT 3X5 LTR

Is accessory to

778993  
OILSPILL MARPOL KIT 12 BARREL(2 PALLETS)  
778914  
OILSPILL MARPOL KIT 7 BARREL(2 PALLETS)

Is consumable by

778862  
UNITOR 4 CHEMICALS DILUTION STATION  
778922  
OILSPILL MARPOL KIT1 BARREL(1 PALLET)  
737189  
CHEM. CLEAN. UNIT W/HEATING, COATED  
2009029  
NAVADAN ULTIMATE KIT  
2009025  
NAVADAN PANAMAX KIT  
2009026  
NAVADAN ESSENTIAL KIT

Is frequently bought together with

2009034  
NAVADAN PROTECTION KIT  
765018  
ENVIROCLEAN 25 LTR  
571321  
ULTRACLEAN GO 25 LTR  
571646  
DESCALEX 25 KG