

Last updated: 05/02/2026 14:29:57

COMMISSIONING CLEANER 25 LTR

Product group: **651** Product number: **624932**

Unitor™ Commissioning Cleaner is an innovative multifunctional water based cleaner that removes scale, rust, oil and grease all in just one step.



Product information

Unitor™ Commissioning Cleaner is the new generation in one step cleaner products. It is designed for cleaning of boiler or cooling systems especially on board new buildings.

The product is recirculated through the systems, using an external circulation pump. Unitor™ Commissioning Cleaner is low foaming and will remove scale, rust, oil and grease at the same time.

Features

- Water based multifunctional cleaner
- Biodegradable
- Low foaming
- Does not contain nonylphenol ethoxylates or other estrogenic compounds
- Cleaning of new systems for mill scale, rust, oil etc.

Benefits

- Cleans water systems with light scale and a thin oil film
- Provides a temporary protection against corrosion by passivation
- Safe on aluminium, zinc, tin and their alloys
- Quick separation of oil after cleaning
- No need of neutralization chemicals afterwards

Specification

General

Invent Hazard Material (IMO/EU) classification	C-49
---	------

Physical properties

Appearance	Off white to pale yellow
Density [g/ml]	1,10 -1,12
Form	Liquid
pH	8,5-9,0 in 20% solution

Documents

[SDoC and MD for IHM](#)

Directions for use

Unitor™ Commissioning Cleaner™ is for cleaning of new boilers and cooling systems on board new buildings. It will remove scale, rust, oil and grease at the same time from the systems. The product is recirculated through the system, using an external circulation pump. Use the dosage 3-10% solution depending on the grade of contamination.

Degreasing and descaling of boiler and cooling water systems

The Unitor™ Chemical Cleaning Unit - Product no. **572060** - is recommended to be used.

Drain system to be cleaned if necessary.

Inspect as completely as possible to determine the extent of contamination and general condition of system.

Fill with fresh water.

Add a solution 3-10% strength of Unitor™ Commissioning Cleaner™.

Circulate through the system for 5 to 8 hours at the maximum temperature allowed by the system.

Drain system complete and flush thoroughly the entire system and all compounds with fresh water until effluent is clear.

Reinspect to determine results of the cleaning process.

If unsatisfactory, repeat steps 3 through 7.

Refill system with distillate or good quality fresh water and dose the required amount of cooling or boiler water treatment.

Test system on a regular basis to insure chemical residuals are maintained with specific limits.

Related products

Is consumable by

778862

UNITOR 4 CHEMICALS DILUTION STATION

737189

CHEM. CLEAN. UNIT W/HEATING, COATED

572060

UNITOR CHEMICAL CLEANING UNIT

Is frequently bought together with

765018

ENVROCLEAN 25 LTR

575613

AQUABREAK PX.25 LTR

607826

AQUATUFF 25 LTR

680843

COOLTREAT AL 25 LTR

571356

ROCOR NB LIQUID 25 LTR

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/commissioning-cleaner-25-ltr/>