

Last updated: 30/04/2025 05:21:10

# DECK CLEAN NP 25 LTR

Product group: 651      Product number: 765990

Unitor<sup>TM</sup> Deck Clean NP<sup>TM</sup> is a liquid cleaning formulation containing acids, emulsifiers and passivators used for removal of rust and water born stains on superstructure and decks.



## Product information

This product supersedes product no: L763953

Unitor<sup>TM</sup> Deck Clean NP<sup>TM</sup> is free of phosphoric acid and is readily biodegradable.

### Features

- Waterborne
- Removes light rust and rust stains from painted and wooden surfaces, metals and glass.
- Does not contain nonylphenol ethoxylates or other estrogenic compounds.
- Phosphoric acid free
- Readily biodegradable
- Non-flammable

### Benefits

- Highly concentrated
- Removes waterborne stains from windows
- Removes light rust and rust stains from painted and wooden surfaces, metals and glass.
- Easy to rinse off

## Specification

### General

Invent Hazard Material (IMO/IU) classification	C-49
--	------

### Physical properties

Appearance	Light yellow
Density [g/ml]	1,1
Form	Liquid
pH	2 in 1% solution

### Technical data

Not Compatible	Long term exposure may lead to corrosion of mild steel, cast iron, aluminium and alloys, brass, tin or galvanized material.
----------------	---

## Approvals

This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

## Documents

[SDoC and MD for IHM](#)

## Directions for use

### Dosage and control

Unitor<sup>TM</sup> Deck Clean NP<sup>TM</sup> should always be added to water, never the reverse. Remove dirt, rust flakes and oil/grease prior to using Unitor<sup>TM</sup> Deck Clean NP<sup>TM</sup>. Required dosage may vary slightly depending on degree of stain.

For the removal of rust stains on painted surfaces & wood, Unitor<sup>TM</sup> Deck Clean NP<sup>TM</sup> should be applied at full strength for heavy stains or diluted to 10-30% strength for light stains.

Allow to soak for 20-30 minutes and rinse off surface with water. A second application may be necessary to remove the stubborn stains.

Unitor<sup>TM</sup> Deck Clean NP<sup>TM</sup> can be used for brightening of teak, mahogany and oak decking and to remove rust and water stains on Wood and Varnished wood.

Make up to a 10% solution of Unitor™ Deck Clean NP™ and allow to soak for about 20 minutes and rinse of surface with water. Do not let Unitor™ Deck Clean NP™ dry on surface.

Related products

Is consumable by

778862  
UNITOR 4 CHEMCALS DILUTION STATION

Is frequently bought together with

765018  
ENVIROCLEAN 25 LTR  
575613  
AQUABREAK PX 25 LTR