

Last updated: 05/02/2026 14:25:44

DECK CLEAN NP 25 LTR

Product group: **651** Product number: **765990**

Unitor™ Deck Clean NP is a liquid cleaning formulation containing acids, emulsifiers and passivators used for removal of rust and water born stains on superstructure and decks.



Product information

This product supersedes product no: **L763953**

Unitor™ Deck Clean NP is free of phosphoric acid and is readily biodegradable.

Features

- Waterborne
- Removes light rust and rust stains from painted and wooden surfaces, metals and glass.
- Does not contain nonylphenol ethoxylates or other estrogenic compounds.
- Phosphoric acid free
- Readily biodegradable
- Non-flammable

Benefits

- Highly concentrated
- Removes waterborne stains from windows
- Removes light rust and rust stains from painted and wooden surfaces, metals and glass.
- Easy to rinse off

Specification

General

| | |
|---|------|
| Invent Hazard Material (IMO/EU) classification | C-49 |
|---|------|

Physical properties

| | |
|-----------------------|------------------|
| Appearance | Light yellow |
| Density [g/ml] | 1,1 |
| Form | Liquid |
| pH | 2 in 1% solution |

Technical data

| | |
|-----------------------|---|
| Not Compatible | Long term exposure may lead to corrosion of mild steel, cast iron, aluminium and alloys, brass, tin or galvanized material. |
|-----------------------|---|

Approvals

This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

Documents

[SDoC and MD for IHM](#)

Directions for use

Dosage and control

Unitor™ Deck Clean NP™ should always be added to water, never the reverse. Remove dirt, rust flakes and oil/grease prior to using Unitor™ Deck Clean NP™. Required dosage may vary slightly depending on degree of stain.

For the removal of rust stains on painted surfaces & wood, Unitor™ Deck Clean NP™ should be applied at full strength for heavy stains or diluted to 10-30% strength for light stains.

Allow to soak for 20-30 minutes and rinse off surface with water. A second application may be necessary to remove the stubborn stains.

Unitor™ Deck Clean NP™ can be used for brightening of teak, mahogany and oak decking and to remove rust and water stains on Wood and Varnished wood.

Make up to a 10% solution of Unitor™ Deck Clean NP™ and allow to soak for about 20 minutes and rinse of surface with water. Do not let Unitor™ Deck Clean NP™ dry on surface.

Related products

Is consumable by

778862

UNITOR 4 CHEMICALS DILUTION STATION

Is frequently bought together with

765018

ENVIROCLEAN 25 LTR

575613

AQUABREAK PX 25 LTR

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/deck-clean-np-25-ltr/>