

# ENVIROCLEAN 25 LTR

Product group: **652**    Product number: **765018**

Unitor™ Enviroclean™ is a micro emulsion water based cleaner and degreaser for general engine room and deck cleaning tasks.



## Product information

This product supersedes product no: **571398,, 571380**

Unitor™ Enviroclean™ is highly concentrated, low toxic, biodegradable and safe to use. It is based on powerful fatty acid derivatives linked with an advanced surfactant formulation.

The main applications are for cleaning and degreasing in the engine room, deck cleaning and for general removal of grease, oil, sludge, polymer compounds, carbon deposits, dirt and grime.

### Features

- Highly concentrated water based degreaser
- Does not contain nonyl phenol ethoxylates or other estrogenic compounds
- Low-toxic
- Unitor™ Enviroclean™ has numerous general marine cleaning applications including the removal of greases, oil, sludge, polymer compounds, carbon deposits, dirt and grime
- As an engine room cleaner it is exceptional as not only can it be used for degreasing, cleaning paint work and carbon removal, but also for use in soak tanks, ultrasonic tanks and high pressure cleaning equipment

### Benefits

- Promotes a pleasant and healthy working environment
- Splits after cleaning, releasing the oil phase for reclamation

## Specification

### General

<b>Invent Hazard Material (IMO/EU) classification</b>	C-49
<b>Product catalog URL</b>	<a href="https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/enviroclean-25-ltr/?epieditmode=true">https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/enviroclean-25-ltr/?epieditmode=true</a>

### Physical properties

<b>Appearance</b>	Pale yellow liquid
<b>Density [g/ml]</b>	1,01 - 1,02
<b>Form</b>	Liquid
<b>pH</b>	10,0 - 11,0

### Technical data

<b>Compatibility</b>	May soften some rubber and synthetic rubber
----------------------	---

## Approvals

Nordic Swan eco-labelled.

This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

## Documents

[SDoC and MD for IHM](#)

## Directions for use

### 1. General cleaning

Unitor™ Enviroclean can be used for all types of cleaning and degreasing and can be applied by brush, hand spray or used in ultrasonic cleaning tanks.

Dependent on the amount and type of soil to be removed typical dosage is about 1-5 %.

After use as an engine room cleaner, bilge slops must be given sufficient time to separate before passing through an oily water separator.

For safe handling and optimal dilution we recommend the use of the UNITOR™ MIXING STATION 4-14.

### 2. Spot cleaning

Unitor™ Enviroclean can be diluted with water and hand sprayed. Recommended dosage up to 25 %, depending on the amount and type of soil to be removed. Left for about 20-30 minutes before washing off with water.

## Related products

### Is accessory to

**766956** ULTRASONIC CLEANER S-3300/HM, 440V

### Is frequently bought together with

**571356** ROCOR NB LIQUID 25 LTR

**698720** AUTOTREAT - 25 LTR

**571752** NATURAL HANDCLEANER 4X5 LTR

**571364** VAPTREAT 25LTR

**589945** GAMAZYME BTC 12 X 1 LTR

### This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/enviroclean-25-ltr/>