

Last updated: 05/02/2026 14:35:03

HP WASH 25 LTR

Product group: **651** Product number: **571729**

Unitor™ HP Wash is an alkaline water based cleaner with detergents and surfactants which quickly dissolve grease and dirt deposits on board. It is designed for use with high pressure cleaning machines.



Product information

Unitor™ H.P. Wash is a phosphate free cleaner, designed for use with high pressure cleaning machines such as Unitor™ High Pressure Cleaners. It is also suitable for hot or cold high pressure spray equipments.

Unitor™ H.P. Wash is also suitable for most painted surfaces and dries leaving a good shine.

Features

- Reformulated with improved cleaning properties and highly concentrated
- Does not contain nonyl phenol ethoxylates or other estrogenic compounds
- Biodegradable & non flammable cleaner
- Can be used for general cleaning in the engine room, outside paint work and on the deck
- Can be used on Ro/Ro vessel car decks, for removal of traffic film
- Can be used for cleaning of fish holds and process machinery onboard factory vessels

Benefits

- Leaves a good shine on hard surfaces after cleaning
- Low dose rates of 0.5-5%
- Rapid dispersal of a large range of oils and greases.

Specification

General

Invent Hazard Material (IMO/EU) classification	C-49
---	------

Physical properties

Appearance	Colorless to pale yellow
Density [g/ml]	1,1
Form	Liquid
pH	12-13

Technical data

Not Compatible	In concentrated form, may react with aluminium, zinc, tin and their alloys. May swell natural and synthetic rubber.
-----------------------	--

Approvals

Nordic Swan eco-labelled.

This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

Approved by Marinflocc AB for use in engine rooms

Documents

[SDoC and MD for IHM](#)

Directions for use

Dosing method

For high pressure cleaning, apply the cleaning agent in an even layer using low pressure. Allow solution to penetrate soil for about 3-5 minutes before washing off thoroughly with high pressure water.

The recommended dose rates for the application using low pressure side of the cleaning machine, is between 0.5-5% depending on amount and type of soil.

Unitor™ H.P. Wash™ can be used by conventional cleaning using brush, rag or spray at a dose rate of 5–20% in water depending on the soiling. Allow 5 minutes for penetration, then rinse off with water.

Sampling and testing

Unitor™ H.P. Wash™ is suitable for most painted surfaces and dries leaving a good shine.

Related products

Is accessory to

777888
UNITOR HPC 67/1 3x400/50Hz

777889
UNITOR HPC 67/1 3x440/60Hz

729333
UNITOR HPC 30/1 220V/60Hz

Is consumable by

729474
UNITOR HPCH 61 HW, 210BAR 220/440V

729402
UNITOR HPC STATIONARY 2P

729333
UNITOR HPC 30/1 220V/60Hz

777886
UNITOR HPC 54/1 3x440/60Hz

729401
UNITOR HPC STATIONARY 1P

777889
UNITOR HPC 67/1 3x440/60Hz

777888
UNITOR HPC 67/1 3x400/50Hz

729403
UNITOR HPC STATIONARY 3P

729404
UNITOR HPC STATIONARY 4P

651100
HPC SOLAR BOOSTER WITH 18KW HEATER

729406
UNITOR HPC STATIONARY 6P

Is frequently bought together with

571752
NATURAL HANDCLEANER 4X5 LTR

607826
AQUATUFF 25 LTR

765018
ENVIROCLEAN 25 LTR

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/hp-wash-25-ltr/>