

Last updated: 30/04/2025 05:22:47

HP WASH 25 LTR

Product group: 651 Product number: 571729

Unitor™ HP Wash™ is an alkaline water based cleaner with detergents and surfactants which quickly dissolve grease and dirt deposits on board. It is designed for use with high pressure cleaning machines.



Product information

Unitor™ H.P. Wash™ is a phosphate free cleaner, designed for use with high pressure cleaning machines such as Unitor™ High Pressure Cleaners. It is also suitable for hot or cold high pressure spray equipments.

Unitor™ H.P. Wash™ is also suitable for most painted surfaces and dries leaving a good shine.

Features

- Reformulated with improved cleaning properties and highly concentrated
- Does not contain nonyl phenol ethoxylates or other estrogenic compounds
- Biodegradable & non flammable cleaner
- Can be used for general cleaning in the engine room, outside paint work and on the deck
- Can be used on Ro/Ro vessel car decks, for removal of traffic film
- Can be used for cleaning of fish holds and process machinery onboard factory vessels

Benefits

- Leaves a good shine on hard surfaces after cleaning
- Low dose rates of 0.5-5%
- Rapid dispersal of a large range of oils and greases.

Specification

General

Invent Hazard Material (IMO/IU) classification	C-49
--	------

Physical properties

Appearance	Colorless to pale yellow
Density [g/ml]	1,1
Form	Liquid
pH	12-13

Technical data

Not Compatible	In concentrated form, may react with aluminium, zinc, tin and their alloys. May swell natural and synthetic rubber.
----------------	--

Approvals

Nordic Swan eco-labelled.

This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

Approved by Marinfloc AB for use in engine rooms

Documents

[SDoC and MD for IHM](#)

Directions for use

Dosing method

For high pressure cleaning, apply the cleaning agent in an even layer using low pressure. Allow solution to penetrate soil for about 3-5 minutes before washing off thoroughly with high pressure water.

The recommended dose rates for the application using low pressure side of the cleaning machine, is between 0.5-5% depending on amount and type of soil.

Unitor™ H.P. Wash™ can be used by conventional cleaning using brush, rag or spray at a dose rate of 5–20% in water depending on the soiling. Allow 5 minutes for penetration, then rinse off with water.

Sampling and testing

Unitor™ H.P. Wash™ is suitable for most painted surfaces and dries leaving a good shine.

Related products

Is accessory to

777888
UNITOR HPC 67/1 3x400/50Hz

777889
UNITOR HPC 67/1 3x440/60Hz

729333
UNITOR HPC 30/1 220V/60Hz

Is frequently bought together with

571752
NATURAL HANDCLEANER 4X5 LTR

607826
AQUATUFF 25 LTR

765018
ENVIROCLEAN 25 LTR