

Product group: 651 Product number: 571661

Unitor™ Metal Brite™ is a liquid detergent compound containing rust dissolving acids, emulsifiers and passivators.

## **Product information**

Unitor™ Metal Brite™ is a non-flammable rust stain remover and surface brightener.

#### **Features**

- Does not contain nonyl phenol ethoxylates or other estrogenic compounds
- Non-flammable
- Surface brightening

#### **Benefits**

- Prevents flash rusting
- · Surfaces rendered suitable for painting

#### **Specification**

#### General

# Invent Hazard Material (IMO/EU) classification C-11

# Physical properties

Appearance	Light yellow
Density [g/ml]	1,2
Form	Liquid
рН	

#### Technical data

Not	Long term exposure will cause corrosion of mild steel, cast iron, aluminium	
Compatible	and alloys, brass, tin or galvanized material	

#### **Approvals**

This composition meets the criteria for not being harmful to the marine environment according to MARPOL Annex V and may be discharged into the sea when used to clean cargo holds and external surfaces on ships.

# Documents

SDoC and MD for IHM

# Directions for use

Unitor™ Metal Brite™ should always be used in a plastic bucket. The acid should always be added to water, never the reverse.

For removal of rust stains and oxide stains on aluminium, brass, copper and stainless steel, apply Unitor™ Metal Brite (after removal of oil and grease) neat with a brush, rag, etc. Wash off after 15 minutes. Repeat if necessary. Do not let Unitor™ Metal Brite™ dry on surfaces as it may leave a hard white deposit.

For steel surfaces remove oil, grease and old paint. Wet down the entire surface with neat Unitor  $^{\text{TM}}$  Metal Brite  $^{\text{TM}}$  and allow to dry. Second wash may be necessary. Surface should have a grey/white appearance when the Unitor  $^{\text{TM}}$  Metal Brite  $^{\text{TM}}$  is dry. Steel surfaces will have a resistance to rust and will render a good base for paint.

For removal of rust stains on painted surfaces and wood, Unitor™ Metal Brite™ should be applied at full strength for heavy stains, or diluted to 30--50% for light stains. Allow to soak for 20 to 30 minutes and wash off with water. A second application may be necessary to remove the stubborn stains.

# Related products

### Is frequently bought together with

571752

NATURAL HANDCLEANER 4X5 LTR

607826

AQUATUFF 25 LTR

765018

**ENVIROCLEAN 25 LTR** 

734781

SAFE CHEMICAL HANDLING PROTECTION PPE KIT

## This page is printed from:

https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/metal-brite-25-ltr/linearing-chemicals/cleaning-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-25-ltr/linearing-and-maintenance/metal-brite-and-mai

