

ALKLEEN LIQUID 25 LTR

Product group: **652** Product number: **756254**

Unitor™ Alkleen Liquid™ is a heavy duty water based alkaline tank cleaner, containing natural based detergents. For zinc silicate coatings use Unitor™ Alkleen Safety Liquid™



Product information

This product supersedes product no: **571539**

Unitor™ Alkleen Liquid™ is a powerful cleaner for cleaning of cargo tanks after discharge of drying, semi-drying and non-drying natural oils and fats. Unitor™ Alkleen Liquid™ can be used for tank sanitising and deodorising prior to changing to foodstuffs. To achieve the high standard of cleanliness required, a final wash will be necessary by using this product.

Unitor™ Alkleen Liquid™ has been evaluated by the BLG Working Group on the Evaluation of Safety and Pollution Hazards of Chemicals (ESPH) and found to meet the requirements of paragraph 13.5.2 of the MARPOL Annex II and is consolidated into annex 10 of the MEPC.2/Circular.

Features

- Powerful alkaline tank cleaner containing detergents
- The emulsifying agents are biodegradable
- Non-flammable
- Non-corrosive to ferrous metals and epoxy coatings
- IMO approved and listed in Annex 10 of the MEPC.2/Circular

Benefits

- Rapid penetration and emulsification of vegetable, animal and fish oils with rapid rinsing
- Removes hardened oxidised oil and grease deposits and can be used as heavy duty cargo tank cleaner following discharge of drying, semi-drying and non-drying natural oils and fats
- Can also be used as final treatment for cleaning tank from black to white or grain
- Can be used for hydrocarbon freeing of cargo tanks

Specification

General

Invent Hazard Material (IMO/EU) classification	C-49
---	------

Physical properties

Appearance	Pale yellow
Density [g/ml]	1,2
Form	Liquid
pH	13

Technical data

Not Compatible	Corrosive to aluminium, magnesium, zinc and tin.
-----------------------	--

Performance data

Pump Speed [cpm]	
-------------------------	--

Variants

Product name	Product number	Not Compatible
ALKLEEN LIQUID 210 LTR	756255 (supersedes 571547)	Corrosive to aluminium, magnesium, zinc and tin.
ALKLEEN LIQUID 25 LTR	756254 (supersedes 571539)	Corrosive to aluminium, magnesium, zinc and tin.

Approvals

Unitor™ Alkleen Liquid™ has been evaluated by the BLG Working Group on the Evaluation of Safety and Pollution Hazards of Chemicals (ESPH) and found to meet the requirements of paragraph 13.5.2 of the MARPOL Annex II and is consolidated into annex 10 of the MEPC.2/Circular.

Documents

[SDoC and MD for IHM](#)

Directions for use

Immediately after use the cargo has been discharged, the tanks should be flushed with cold water to prevent polymerisation and evaporation of the lighter fractions. Whenever possible, the cleaning solution of 0.2-3% in fresh water should be heated to 60-80°C. However, the polymerising nature of some natural oils demand lower cleaning temperatures.

Dosing method

The most economical method to use UNITOR™ Alkleen Liquid™ is by direct injection followed by recirculation washing by using tank cleaning machines.

If this method is not possible, use of other methods such as recirculation or hand spraying.

When changing refrigerated cargoes the need may arise to clean holds to remove animal or vegetable fat to sanitise and deodorise before the next cargo. A solution of 5-10% in fresh water can be used for this purpose, and may be sprayed on and rinsed off by using hot water and high pressure.

Related products

Is frequently bought together with

765018	ENVIROCLEAN 25 LTR	575613	AQUABREAK PX 25 LTR
571661	METAL BRITE 25 LTR		
571356	ROCOR NB LIQUID 25 LTR		
698704	ACC PLUS 25 LTR		

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/tank-cleaning/alkleen-liquid-25-ltr/>